

LC-PA1216	12	16	151	98	99	105	187& 250M
LC-PD1217	12	17	181	76	167	167	M5 L& M5 A
LC-P1220	12	20	181	76	167	167	M5 L& M5 A
LC-P1224	12	24	165	125	175	179.5/175	M5 L& M5 A
LC-P1228	12	28	165	125	175	179.5/175	M5 L& M5 A
LC-P1238	12	38	197	165	175	180/175	M6 L& M5 A
LC-P1242	12	42	197	165	175	180/175	M6 L& M5 A
LC-P1265	12	65	350	166	175	175	M6 L
LC-P1275	12	75	350	166	175	175	M6 L
LC-P12100	12	100	407	173	210	236	M8 L
LC-P12120	12	120	407	173	210	236	M8 L
LC-P12150	12	150	532.4	183.3	209	235/214	M8嵌入式铜芯
LC-P12200	12	200	533	236.5	211	237/216	M8嵌入式铜芯
LC-P067R2E	6	7.2	151	34	94	100	187& 250M
LC-P0612E	6	12	151	50	94	100	187& 250M
LC-P127R2E	6	7.2	151	64.5	94	100	187& 2

LC-P系列---后备浮充使用普通品用途:大、中、小型UPS、通讯领域、医疗设备、安全系统等特点:浮充期待寿命6年(25)/10年(20);更高比能量;采用***阻燃材ABS槽壳,符合UL94V-0标准,降低壳体燃烧可能;