

500W带PFC 恒流工业开关电源 舞台灯光电源 大功率工控设备电源

产品名称	500W带PFC 恒流工业开关电源 舞台灯光电源 大功率工控设备电源
公司名称	深圳市恒俊丰科技有限公司
价格	1.00/件
规格参数	品牌:恒俊丰科技 型号:H25 产地:深圳
公司地址	深圳市宝安区福永街道白石厦社区东区泰原工业园4栋302
联系电话	18123907582

产品详情

品牌恒俊丰 (HJF)

产品类型电源板

安装方式螺丝

产品认证ROHS

重量800G

外形尺寸140*82*38

工作效率93

产品系列H25

输入电压范围90-265

工作频率47-63

工作温度-20-45

H25 500W开关电源

H25 500W SWITCHING POWER SUPPLY

高品质高性价比

HIGH QUALITY HIGH COST-EFFECTIVE

高效环保

HIGH EFFICIENCY, ENVIRONMENT-FRIENDLY

过载短路保护

OVERLOAD SHORT CIRCUIT PROTECTION

自然风冷却

VENTILATION COOLING(230V)

****负载老化

**** LOAD AGING TEST

* 外形尺寸DIMENSION :

H25 160*65*42mm

* 输入INPUT VOLTAGE RANGE :

100-240VAC ;

* 频率FREQUENCY RANGE:

47-63HZ

* 耐压WITHSTANDING VOLTAGE :

输入INPUT-机壳CASE:1.5KVac

* 工作环境ENVIRONMENTAL REQUIREMENT :

-20-45 , 20%-90%RH

Safety (安全规格)

Power safety reference the following standards

电源安全性参考下列标准:

- 1) *UL60950/UL60065
- 2) *EN60950/EN60065
- 3) *GB4943-1995/GB8898-2001

EMC (电磁兼容性)

1.1 EMI (电磁干扰)

The power supply shall comply with the following criterion:

电源电磁干扰满足下列标准：

1) Conduction Emission : (传导干扰度)

*EN55013/EN55022, CLASS B

*GB13837-2003, CLASS B

*CISPR13:2001/FCC PART15 CLASS B

2) Radiated Emission : (辐射干扰度)

*EN55013/EN55022, CLASS B

*GB13837-2003, CLASS B

*CISPR13:2001/FCC PART15 CLASS B

Note : The power board should be assembled in customer product to test for passing the above criterion.需配合用户电路整机通过上述标准。

1.2 EMS (电磁抗扰)

The power supply shall comply with the following criterion:

电源电磁抗扰满足下列标准：

1) ESD (静电抗扰度)

*GB17626.2-1998/IEC61000-4-2 Lever 3

2) EFT (脉冲群抗扰度)

*GB17626.4-1998/IEC61000-4-4 Lever 3

3) SURGE (雷击浪涌)

*GB17626.5-1998/IEC61000-4-5 Lever 3

4) DIP (电压跌落)

*GB17626.11-1998/IEC61000-4-11 Class B/C