

碳素盘根一级耐磨损，强酸碱碳素盘根，化工厂盘根

产品名称	碳素盘根一级耐磨损，强酸碱碳素盘根，化工厂盘根
公司名称	廊坊通宁节能科技有限公司
价格	.00/件
规格参数	品牌:通宁 材质:碳素纤维 河北:廊坊
公司地址	河北省廊坊市大城县广安镇郝家屯村
联系电话	18230346131 18230346131

产品详情

Carbon Fiber Packing Impregnation in Graphite

Item:GP322,GP322K

PDF:

Description:

GP322 Carbon Fiber Packing (Impregnation in graphite particle) each carbon fiber is treated with graphite particles and then is diagonal braided to form packing. Compared to most other packing, GP312 enough to handle most high temperature applications. GP312 has a low coefficient of friction thus reducing drag on shafts and wear on the same.

It is premium service packing for steam water. Petroleum, oils, acids and many solutions.

The series of products as follows:

GP322 Carbon Fiber Packing (Impregnation in graphite particles)

GP312 Carbonize Fiber Packing (Impregnation in graphite particles)

APPLICATION:

The packing is diagonal braided to form a dense but pliable packing, further enhanced with blocking agents. Easy installation and extrusion resistance in single-spool packing. Special for high pressure. High temperature steam service.

PARAMETER:

Technical data Rotating Reciprocating Valves

Pressure (Mpa) 3 10 30

Shaft speed (m/s) 0~20

Sulfur content Chlorine content

Temperature (°) -250~650

PH range 0~14

GP322K is the similar packing like GP322. While the carbon fiber is inserted with Inconel to increase its pressure resistance.

PARAMETER:

Technical data Rotating Reciprocating Valves

Pressure (Mp) 20 40

Shaft speed (m/s) 0~10

Sulfur content Chlorine content

Temperature (°) -250~650

PH range 0~14

PACKAGE

In coils of 5 kg, 10kg, 25kg, other packages on request.

Supply OEM products.