

## 换热器用带环金属垫，B型带内环金属缠绕垫，齿形垫圈

产品名称	换热器用带环金属垫，B型带内环金属缠绕垫，齿形垫圈
公司名称	廊坊通宁节能科技有限公司
价格	.00/件
规格参数	品牌:通宁 材质:金属 河北:廊坊
公司地址	河北省廊坊市大城县广安镇郝家屯村
联系电话	18230346131 18230346131

### 产品详情

#### 换热器用带环金属垫，B型带内环金属缠绕垫，齿形垫圈

.内外环材料 常用的有304SS,316LSS,321SS,347SS,碳钢,钛,铜. mix: The flange on the pad designs to facilitate the installation of the Company under the gasket-caliber size, the gasket external welding a 2 ~ 8 positioning belt buckle for positioning hole in the flange, to prevent displacement installation gasket or falling out of the supporting material and saving hours of work. Types and gasket materials 1, Winding pads divided into four forms: that is, as the basic type A, B band strengthen ring, the C-band to strengthen the ring, the D-band, the strengthening ring. 2, the general use of materials A strip: 0Cr13, 0Cr18Ni9 (304), 0Cr18Ni9Ti, [1Cr18Ni9Ti](#) (321), 0Cr17Ni12Mo2 (316), 00Cr17Ni14Mo2 (316L) B, both inside and outside ring materials are A3, 304,316,316 L C, non-metallic sandwich belt: Flexible Graphite PTFE, custom-made asbestos. 使用范围：Use of: 1、使用温度：-196 -650 1, the use of Temperature: -196 ° C -650 ° C (氧化介质中不高于450 ) Oxidation medium does not exceed 450 ° C) 2、使用压力 26MPa 2, the use of pressure 25MPa 3、垫片厚度：2.5-4.5mm 3, gasket thickness :2.5-4.5 mm 性能：1、适用范围广。能耐高温、高压和适应超低温或真空下使用。 2、应用补偿能力强。在高温、高压波动频繁的工位上，密封性能稳定、可靠性强。 3、有良好的密封性能。 4、使用安装方便。 Performance: 1, the scope of application-Canton. Can high temperatures, high pressure and adapt to ultra-low-temperature vacuum or use. 2, the ability of compensation. At high temperature, high pressure fluctuations frequent-position, the sealing performance stability and reliability. 3, a good sealing performance. 4, the use of the installation convenience

#### 换热器用带环金属垫，B型带内环金属缠绕垫，齿形垫圈