

## C00二手Bio-rad C100 PCR仪

产品名称	C00二手Bio-rad C100 PCR仪
公司名称	天津金思德生物有限公司
价格	面议
规格参数	
公司地址	天津市东丽区华明镇南坨工业园广源路13号
联系电话	022-84901689 15302050081

## 产品详情

The C1000™ thermal cycler is a state-of-the-art instrument that accommodates multiple sample formats. The instrument is equipped with a large, easy-to-use graphical interface for easy programming, protocol optimization, and monitoring and tracking runs. For truly sophisticated applications, the C1000 thermal cycler can be upgraded for real-time quantitative PCR.

Key features:

- o Precision temperature control

- o Fast and easy protocol

性能参数：

显示屏12 x 9 cm, 高分辨率，全彩色

接口5 USB-A；1 USB-B

适配USB 闪存是

适配USB 鼠标是

程序编写选项图形，文本，自动程序编写器

自动程序编写器是

报告可以输出的运行日志、系统报错日志

安全性能保护模式，登录选项，文件夹保护

温度控制模式逻辑算法和模块温度控制

升级为定量PCR 仪是

PCR 证书有

在线软件Windows CE 6.0

和工作站适配是

储存大于1000个程序，USB 扩展

保温功能有

大小 (W X D X H) 13 " x18 " x8 "

重量23 lbs

温度梯度精确性\*  $\pm 0.2^{\circ}\text{C}$

温度梯度行均一性\*  $\pm 0.4^{\circ}\text{C}$

温度梯度范围\*30 – 100  $^{\circ}\text{C}$ , 不低于室温30  $^{\circ}\text{C}$

温度梯度温差范围1-24  $^{\circ}\text{C}$

电压范围100 – 240 VAC (在此范围内，电压无需调整)

频率50 – 60 Hz

输出功率最大 400 W

保险丝2个，6.3 A, 250 V, 5 x 20 mm

96 孔快速模块48/48 孔快速模块

样品容量96x 0.2mL

温度梯度功能有

温度梯度范围30-100  $^{\circ}\text{C}$

温度梯度温差范围1-24  $^{\circ}\text{C}$

温度梯度精确度  $\pm 0.2^{\circ}\text{C}$

温度梯度均一性  $\pm 0.4^{\circ}\text{C}$  (90  $^{\circ}\text{C}$  时维持10秒钟)

热盖温度范围0-110 ° C

最大升降温速率5 ° C/秒