

欧盟标准 EN 16434 内窗帘,防止勒颈窒息危险-安全器件要求和测试方法

产品名称	欧盟标准 EN 16434 内窗帘,防止勒颈窒息危险-安全器件要求和测试方法
公司名称	深圳市实测通技术服务有限公司
价格	.00/件
规格参数	测试周期:5-7天 寄样地址:深圳宝安 价格费用:电话详谈
公司地址	深圳市罗湖区翠竹街道翠宁社区太宁路145号二单元705
联系电话	17324413130 17324413130

产品详情

EN 16434, 内窗帘, 防止勒颈窒息危险 安全器件要求和测试方法 Internal blinds - Protection from strangulation hazard
Test methods for safety devices

条款 Clause	测试项目 Test item
Tensioning device 张紧构件	
5	Artificial ageing 人工老化: Exposure to UV 紫外线老化 Mechanical endurance 机械寿命 Exposure to high/low temperature 高低温
6	Functional performance 功能性测试 Note: Perform after original condition, UV, endurance, high/low temperature 原始条件和老化后各试验一次
11.2	Release of small components 小部件测试
11.3	Impact resistance 冲击测试 Note: Perform after UV, high/low temperature UV 和高低温后各试验一次
Breakaway device 分离构件	
5	Artificial ageing: Exposure to UV 紫外线老化 Mechanical endurance 机械寿命, Exposure to high/low temperature 高低温
7	Functional performance 功能性测试 Note: Perform after original condition, UV, endurance, high/low temperature 原始条件和老化后各试验一次

11.2	Release of small components 小部件测试
	Accumulation device 积线构件
5	Artificial ageing 人工老化: Exposure to UV 紫外线老化 Mechanical endurance 机械寿命 (for with mo Exposure to high/low temperature 高低温
8	Functional performance 功能性测试 Note: Perform after original condition, UV, endurance, high/lo 原始条件和机械寿命后各试验一次
11.2	Release of small components 小部件测试
11.3	Impact resistance 冲击测试 Note: Perform after UV, high/low temperature UV和高低温后各试验一
	Non tangling device 防缠结构件
9	Functional performance 功能性测试
11.2	Release of small components
	Inner cord stop 内线止动构件
5	Artificial ageing 人工老化: Exposure to UV 紫外线老化
10	Functional performance 功能性测试
11.2	Release of small components 小部件测试
测试时间 Test time	含老化和机械寿命 (incl. UV & Mechanical endurance) : 35 工作日 Working days 不含老化和机械寿命 (Mechanical endurance) : 12 工作日 Working days
样品要求 Sample required	三套有代表性的窗帘样品和10 m长度拉绳 Three representative blind product and 10 m pull cord, including: 张紧构件 Tensioning device: 10个 (pieces) 分离构件 Breakaway device: 10个 (pieces) 积线构件 Accumulation device: 5个 (pieces) 防缠结构件 Non tangling device: 3对 (pairs) 内线止动构件 Inner cord stop: 3个 (pieces)

Sample for reference 参考图片:

>Sample Report 报告样本 :