

欧盟标准 EN 795 防止从高处跌落.抛锚设备测试

产品名称	欧盟标准 EN 795 防止从高处跌落.抛锚设备测试
公司名称	深圳市实测通技术服务有限公司
价格	.00/件
规格参数	测试周期:5-7天 寄样地址:深圳宝安 价格费用:电话详谈
公司地址	深圳市罗湖区翠竹街道翠宁社区太宁路145号二单元705
联系电话	17324413130 17324413130

产品详情

Test or certification item 测试或认证名称: 防止从高处跌落.抛锚设备 Personal fall protection equipment - Anchor devices

EN795-Type A 单一方向样品4个GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomicsdeformation testdynamic strength and integrity teststatic strength testMarkingInformation supplied by the manufacturerEN 795-Type B-except Tripod 单一挂点样品4个GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.2.1 deformation test4.4.2.2 dynamic strength and integrity test4.4.2.3 static strength testMarkingInformation supplied by the manufacturerEN 795-Type B-Tripod except leg anchor 单一挂点不含支架挂点样品4套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.2.1 deformation test4.4.2.2 dynamic strength and integrity test4.4.2.3 static strength testMarkingInformation supplied by the manufacturerEN795-Type B-Tripod include leg anchor 含一个支架挂点样品8套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.2.1 deformation test4.4.2.2 dynamic strength and integrity test4.4.2.3 static strength test4.4.2.4 支架处挂点增加测试/增加EN1496测试MarkingInformation supplied by the manufacturerEN795-Type C-single-span单跨度样品4套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.3.1deformation test4.4.3.3 single-span dynamic strength and integrity test4.4.3.5 static strength testMarkingInformation supplied by the manufacturerEN795-Type C-multi-span except corner 多跨度样品6套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.3.1deformation test4.4.3.3 multi-span dynamic strength and integrity test4.4.3.5 static strength testMarkingInformation supplied by the manufacturerEN795-Type C-multi-span include corner 含拐角样品8套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.3.1deformation test4.4.3.3 multi-span dynamic strength and integrity test4.4.3.5 static strength testMarkingInformation supplied by the manufacturerEN795-Type D-single-span 单跨度样品4套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.4.1 deformation test4.4.4.2 dynamic strength and integrity test (single-span/multi-span) 4.4.4.3 static strength testMarkingInformation supplied by the manufacturerEN795-Type D-multi-span except corner 多跨度样品6套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.4.1 deformation test4.4.4.2 dynamic strength and integrity test (single-span/multi-span) 4.4.4.3 static strength

testMarkingInformation supplied by the manufacturerEN795-Type D-multi-span include a corner 含拐角样品8套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.4.1 deformation test4.4.4.2 dynamic strength and integrity test (single-span/multi-span) 4.4.4.3 static strength testMarkingInformation supplied by the manufacturerEN795-Type D-multi-span include a cantilever 多跨度含悬臂梁 样品6套GeneralMaterials 5.8 Corrsion resistanceDesign and ergonomics4.4.4.1 deformation test4.4.4.2 dynamic strength and integrity test (single-span/multi-span) 4.4.4.3 static strength testMarkingInformation supplied by the manufacturer

Norm refer 涉及法规: PPE/CE

Refer products 涉及产品: 攀岩设备

Lead time 周期: 常规服务 regular service 15 工作日 working days (URGENT service, to be confirm, 加急服务待定)

Sample size 送样规格: 8pcs finished products 八个成品 Sample report 样本报告 :

Photo for reference 涉及图片: