

Model 357C71 充电输出加速器美国PCB PIEZOTRONICS现场选型

产品名称	Model 357C71 充电输出加速器美国PCB PIEZOTRONICS现场选型
公司名称	上海持承自动化设备有限公司
价格	8400.00/件
规格参数	品牌:PCB PIEZOTRONICS 型号:357C71 产地:美国
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

产品详情

Model 357C71 充电输出加速器美国PCB PIEZOTRONICS现场选型

CHARGE OUTPUT ACCELEROMETER

Model 357C71

Charge output accel., 10 pC/g, 1000g, to 5 kHz, 2-pin conn., 3-hole mount, to +900 F

Sensor can be paired with any one of the charge amplifiers in the Suggested Accessories section. If paired with a Model Number 422M182, cable Model Numbers 013GNXXXGP and 045M19 should be used. If paired with a Model Numbers 421A30 or EX682A40, cable Model Numbers 013GNXXXGP and 045M21 should be used. Cable Model Number 013GNXXXGP is radiation-hardened for nuclear applications.

Replaces Legacy Model Endevco 6233C-10

Sensitivity: ($\pm 5\%$)10 pC/g (1.02 pC/(m/s))

Measurement Range: ± 1000 g pk (± 9810 m/s pk)

Frequency Range: ($\pm 5\%$)4 kHz (4 kHz)

Weight: 2.6 oz (75 gm)

Specification Notes :

[1] Zero-based, least-squares, straight line method.

[2] Transverse sensitivity is typically 3%.

[3] Low frequency response is determined by external signal conditioning electronics.

[4] Typical.

[5] See PCB Declaration of Conformance PS081 for details.

* All specifications are at room temperature unless otherwise specified.

Build Out Your Measurement Chain :