

# Flowserve logix3200系列数字定位器

产品名称	Flowserve logix3200系列数字定位器
公司名称	北京杰德莱特科技有限公司
价格	24500.00/台
规格参数	
公司地址	北京市朝阳区路67号
联系电话	86-01085501516 13439047862

## 产品详情

### flowserve logix3200系列数字定位器

logix 3200iq 利用先进的压电技术和内回路反馈提供优越的性能、控制和可靠性，同时采用紧凑、轻型和模设计最大程度地降低耗气量。logix 3200iq 用于采用控制阀的行业，例如油气生产和提炼、化学加工以及纸浆和造纸行业。它将继续在全球范围内的新兴市场和地区获得认可

flowserve logix3200系列数字定位器技术参数：

电源供给power supply	two-wire, 4-20 ma input
通讯communications	hart protocol
线性度linearity	0.5% full scale
迟滞hysteresis	0.5% full scale
重复精度repeatability	0.1% full scale
死区deadband	0.1% full scale
工作温度 operating temperature range	standard: -4 ° f to 176 ° f (-20 ° c to 80 ° c) low: -40 ° f to 176 ° f (-40 ° c to 80 ° c)

外壳housing	cast, powder-painted aluminum or stainless steel
重量weight	aluminum: 8.5 lb. (3.9 kg) stainless steel: 20.5 lb. (9.3 kg)

flowserve logix3200系列数字定位器选型表：

selection		code	example
		3	3
协议protocol	hart	2	2
特征diagnostics	standard	0	1
	advanced	1	
材质material	aluminum, white paint (valtek)	0	0
	stainless steel, no paint (valtek)	1	
	aluminum, black paint (automax)	2	
	aluminum, food-grade white paint (automax)	3	
	aluminum, black paint (accord)	4	
	aluminum, food-grade white paint (accord)	5	
设计版本 design version		iq	iq
认证certifications	explosionproof eex d iib + h2, atex ii 2 g (cenelec)	07	10
	explosionproof class i, div 1, groups b, c, d intrinsically safe class i, div 1, groups a through g (fm, csa) fm	10	

	nonincendive. csa class i, div 2, class i, zone 1, group iib + h2 and exia class 1, zone 0, group iic (csa only)		
	general purpose	14	
	intrinsically safe eex ia iic t4, standard temp: -40 ° f (-40 ° c) ta 176 ° f (80 ° c)/131 ° f (55 ° c), atex ii 1 g (cenelec)	15	
	iecex ex d iib + h2	16	
轴shaft	316 stainless steel shaft (valtek standard)	d6	d6
	316 stainless steel (vdi/vde 3845)	n6	
电气接口conduit connections	1/2" npt	e	e
	m20	m	
方式action	four-way (double-acting)	04	04
	three-way (single-acting)	03	
	four-way vented (double-acting)	4v	
	three-way vented (single-acting)	3v	
温度temperature	operating temperature (-40 ° f to 176 ° f; -40 ° c to 80 ° c)	40	40
压力表gauges	gauges (valtek standard)	og	og
	stainless steel gauges	os	
	stainless steel with brass internals (kg/cm2)	kg	
	stainless steel with stainless steel internals (kg/cm2)	ks	
	no gauges	ou	

特殊选项	4-20 ma position feedback	of	of
special options	no specials	oo	