

# Victron充电器 Centaur Charger 12/30 (3)半人马12V30A

产品名称	Victron充电器 Centaur Charger 12/30 (3)半人马12V30A
公司名称	北京狮克电源科技有限公司
价格	.00/件
规格参数	品牌:Victron Energy 型号:Centaur Charger12/30 功率:12V30A
公司地址	北京市昌平区顺沙路88号
联系电话	010-56018769 18612657778

## 产品详情

Victron Centaur Charger 12V/30A(3) 120-240V

The Centaur battery charger features auto-ranging input covering 90-265VAC 50/60Hz input meaning they can be used anywhere in the world. Crucially, and unlike many other products that state universal input, the Centaur battery charger will maintain full output power. Other features include:

Three isolated outputs to simultaneously charge 3 battery banks. Each output is capable to supply the full rated current.

Aluminium epoxy powder coated cases with drip shield and stainless steel fixings withstand the rigors of an adverse environment: heat, humidity and salt air.

Circuit boards are protected with an acrylic coating for maximum corrosion resistance.

Temperature sensors ensure that power components will always operate within specified limits, if needed by automatic reduction of output current under extreme environmental conditions.

The chargers also accept a 90-400 V DC supply.

Three-stage charging, with temperature compensation  
The Centaur charges at bulk rate until the output has reduced to 70% of the rated Amps, at which a 4 hour timer begins. After the timed period the charger switches to float rate. An internal temperature sensor is used to compensate the charge voltage with  $- 2 \text{ mV/C}$  ( $- 1 \text{ mV/F}$ ) per cell. A DIP switch is available to select the optimum charge/float voltages for Flooded Lead-acid, Gel or AGM batteries

Nominal Voltage

12 Volt

Charging Voltage	14.3 V
Charging Current	30 A
Charger Type	3 Stage IUoU
Battery Capacity Range	120 - 300 Ah
Protection category	IP20
Dimensions (mm) H x W x D	355 x 215 x 110
Operating temperature	-20C to +60C