太阳能跟踪控制器 双轴跟踪控制

产品名称	太阳能跟踪控制器 双轴跟踪控制
公司名称	常州润源电子科技有限公司
价格	.00/个
规格参数	
公司地址	天宁区中吴大道1219号
联系电话	86-051986711519 18915019608

产品详情

产品型号：ry-kzq-b

应用范围：针对聚焦电池板（简称：cpv模组）

技术参数：

跟踪精度：± ° 供电方式：双电源供电电源电压：±dc12v（可使用：两节dc12v电池或开关电源）工作电流：<80ma静态电流：<2ma轴数：双轴水平方向：360 ° 俯仰方向：180 ° 跟踪方式：实时跟踪防护特级：ip55接口方式：快速插件外形尺寸：140*85*35重量：约400g特色功能：特色功能1：带有风速检测接口，实时监控风速。选配本公司的ry-fs风速传感器，当遇到大风（≥7级风速）时，系统自动将系统放平，当风速变小后，过一段时间（约20分钟），系统自动恢复到正常工作状态。继续跟踪太阳。特色功能2：过载保护。当系统在极其恶历的环境下使用，外界不确定因素（大暴雨，极低温度-35-40 ° c，水平与俯仰转动部分被冻住；大暴雪，积雪很厚等等因素），系统偿试工作，如果不能工作，系统立即进行保护，防止电机被损坏。特色功能3：限位保护。水平限位保护，外界使用环境千差万别，系统也可能不正常工作，当没有水平限位，系统有可以沿一个方向一直转下去，导致系统的连接线，越绕越多，最后绕断。有水平限位保护时，当系统转到限位处，系统沿原路径返回，彻底解决绕线的问题；俯仰限位，当遇到大风时可以检测系统放平到位检测。特色功能4：自动返回。当太阳下山，天色暗下来，系统会沿原路径自动返回到初始位置，第二天太阳出来就跟踪上，节省寻找太阳的时间，提高了发电量。

solar tracking controller, technical parameters

ry-kzq-btechnical parameters

model specifications	ry-kzq-b
tracking precision:	± 0.3 °

power supply	double power supply
the power supply voltage	±dc12v
the working current	<50ma
static electricity	<2ma
automatic tracking mode	biaxial automatic
range of vertical angle (angle of elevation)	-90 ° ~ +30 ° (加限位)
horizontal angle range (azimuth)	0~355 ° ° (加限位)
shape dimension	140*55*35mm
interface	rapid plug-ins
weight	250gabout
functional description	limitprotectionautomatic returnsoverload protectionwith wind testing interface