

# 欧盟CE认证标准EN 635-3 《胶合板 - 按表面外观分类 - 第3部分：软木》

产品名称	欧盟CE认证标准EN 635-3《胶合板 - 按表面外观分类 - 第3部分：软木》
公司名称	深圳市实测通技术服务有限公司
价格	.00/件
规格参数	测试周期:5-7天 寄样地址:深圳宝安 价格费用:电话详谈
公司地址	深圳市罗湖区翠竹街道翠宁社区太宁路145号二单元705
联系电话	17324413130 17324413130

## 产品详情

标准编号 Standard/Code	标准名称 Standard Title
EN 635-3	Plywood - Classification by surface appearance - Part 3: Softwood

This European Standard specifies the nature and limits of characteristics inherent in wood and manufacturing defects enabling the visual assessment of the plywood for allocation to an appearance class. This classification is a contribution to assessing the finishing suitability of plywood. This part of EN 635 applies to plywood, the surface veneers of which are made from softwood species. It does not apply to overlaid panels.

Test Requirement 测试要求：

3.2.1 Classification according to characteristics inherent in wood 根据木材固有的特性进行分级  
3.2.1.1 Pin knots 针节  
3.2.1.2 Sound intergrown knots 光滑的活节  
3.2.1.3 Unsound or non-adhering knots and knots holes 非光滑或非粘合的节以及节洞  
3.2.1.4 Splits 裂缝  
3.2.1.5 Abnormalities due insects, marine borers and parasitic plants 由昆虫，凿船虫以及寄生物引起的木材异常  
3.2.1.6 Resin pockets and inbark 树脂袋及内皮  
Resin streak 树脂条痕  
3.2.1.7 Irregularities in the structure of the wood 木材结构的不规则  
3.2.1.8 Discoloration which is not wood destroying 非木材损坏引起的变色  
3.2.1.9 Fungal decay, which is wood destroying 木材损坏引起的真菌腐烂  
3.2.1.10 Other characteristics 另外的特性  
3.2.2 Classification according to manufacturing defects 根据制造缺陷进行分级  
3.2.2.1 Open joints 开口接合  
3.2.2.2 Overlaps 重叠  
3.2.2.3 Blisters 水泡  
3.2.2.4 Hollows, imprints and bumps 凹痕，烙印及撞痕  
3.2.2.5 Roughness 粗糙度  
3.2.2.6 Sanding through 砂纸打磨痕  
3.2.2.7 Glue penetration 胶水渗透  
3.2.2.8 Foreign particles 杂志粒子  
3.2.2.9 Repairs 修理  
3.2.2.10 Defects at the edges of the panel due to sanding or sawing 由于打磨或锯切引起的木板边缘缺陷  
3.2.2.11 Other defects 另外的缺陷

Sample Size 样品数量 / 送样规格: 5 pcs Lead Time / TAT (Turn Around Time) 测试周期: 常规服务 Regular service 7-9 working days

Report Summary 报告摘要: