

气动热风隔绝门、不锈钢插板门、煤粉管道插板门

产品名称	气动热风隔绝门、不锈钢插板门、煤粉管道插板门
公司名称	永嘉县巨晨阀门有限公司
价格	1680.00/件
规格参数	型号:PZ673H、X-10P 材质:304不锈钢 性能:耐磨、对夹式
公司地址	永嘉县东瓯街道张堡工业区林洋片段（永嘉县罗浮天龙水泵厂内）
联系电话	13075736182

产品详情

PZ673H、X-10P气动热风隔绝门、不锈钢插板门、煤粉管道插板门主要技术参数和性能：

?????200×200?...?1000×1000?????-10~+200??????GB/T9113?JB/T79?????WCB?Q235A?304?316?
304L?316L????????????????????1?????2?????3?????4????????????0.4~0.6MPa ??????DC24V?AC220V
?????????DC24V?AC220V ???(??????5
0mm)?

??
10mm ???

??
??
??(??????50mm)

??

??Category	AxA	BxB	CxC	L	H	D0	r
??One-way	220×200	256×256	296×296	100	820	300	8-
	250×250	306×306	346×346	100	930	340	8-
	300×300	356×356	396×396	100	1050	380	8-
	400×400	456×456	496×496	100	1140	445	12-
	450×450	510×510	556×556	120	1450	530	12-
	500×500	560×560	606×606	120	1610	580	16-
??Two-way	600×600	660×660	706×706	120	1830	450	16-

	700×700	770×770	820×820	140	2130	450	20
	800×800	870×870	920×920	140	2440	450	20
	900×900	974×974	1030×1030	160	2660	450	24
	1000×1000	1074×1074	1130×113	160	2870	450	24
??Specification	LMD-??LMD one-way	?-??I hand wheel	<p>????M=0.105x-113(x?????????????)?????1.7?????????1.7 ber of chain nodes M = 0.105x-113 (x means the distance lead screw center from surface); use hand wheel if the h less than 1.7 m; use chain wheel if the height is more tha m.</p>				