## Platform steel grating

产品名称	Platform steel grating	
公司名称	安平广森源网业有限公司	
价格	4.00/sq.m	
规格参数		
公司地址	河北省衡水市安平县李各庄工业园区	
联系电话	86-03188067138 15075828590	

## 产品详情

NAME	Platform steel grating
	1, steel grating of flat pitch 30mm is the industry's most versatile varieties. It has the strongest attraction on the surface impact in all the series.
	2, steel grating of flat pitch 40mm is the most economic and portable .In the span of the smallest occasions, is the ideal choice.
	3, flat pitch 60mm, bar spacing of 50mm steel grating is designed for the mining industry in the application, which solves the problem of mineral splashed on the surface, often specified for the mining industry processing factory, transfer station, crushing system board.
	1, in the neighboring additional welded kick plate (flange plate), pattern plate panel, mounting connecting piece and other accessories
	2, in different specifications of the flat edge from flat steel, angle steel, channel steel, square tube or other edge.
	3,it can mounted on the board handles and hinges on move or open steel grating platform.
	4, steel grating edge welding standards are:
	per five welding a series of

	each; four welding a; series		
	every three soldering a.Welds shall be not less than 3mm with fillet weld, weld length 20mm		
USES	General Factory, workshop, mining, port of various platforms can be selected, beautiful style, convenient		
	installation, is a replacement of new building products.		

## Common specifications:

	No.	Item	Description
1		Bearing Bar	25x3, 25x4, 25x4.5, 25x5, 30x3, 30x3, 30x5, 32x5, 40x5, 50x5, 65x5, 75x6 75x10100x10mm etc; I bar: 25x30x5x3, 32x5x3, 40x5x3 etc
			US standard: 1''x3/16'', 1 1/4''x3/1 1/2''x3/16'', 1''x1/4'', 1 1/4''x1/4'', 1/2''x1/4'', 1''x1/8'', 1 1/4''x1/8'', 1 1/2''x1/8'' etc
2		Bearing Bar Pitch	12.5, 15, 20, 23.85, 25, 30, 30.16, 30 34.3, 35, 38.1, 40, 41.25, 60, 80mm
			US standard: 19-w-4, 15-w-4, 11-v 19-w-2, 15-w-2 etc.
3		Twisted Cross Bar Pitch	38.1, 50, 60, 76, 80, 100, 101.6, 120 4'' etc
4		Material Grade	ASTM A36, A1011, A569, Q235, S SS304, Mild steel & Low carbon ste
5		Surface Treatment	Black, self colour, hot dip galvanize painted, spray coating
6		Grating Style	Plain / Smooth, Serrated /teeth, I b serrated I bar
7		Standard	China: YB/T 4001.1-2007, USA: ANSI/NAAMM(MBG531-88),

UK: BS4592-1987, Australia: AS16 Japan:JIS