

Water grate

产品名称	Water grate
公司名称	安平广森源网业有限公司
价格	4.00/sq.m
规格参数	
公司地址	河北省衡水市安平县李各庄工业园区
联系电话	86-03188067138 15075828590

产品详情

NAME	Water grate
MATERIALS	Grey cast iron G-20
TECHNICS	The design can be based on customer requirements change, after the jet black asphalt, product appearance bright, neat, oxidation resistance
CHARACTERITICS	Has strong compressive, bending, impact resistance, heat resistance, cold resistance, abrasion resistance, acid and alkali resistance, aging resistance, not easy to deformation characteristics. At the same time, noise prevention, theft, fall prevention, anti-skid characte
USES	Corrosion products applicable to a wide range, can be used in city construction in the tap water, municipal sewage pipeline inspection well manhole, heating, gas, postal, telecommunications, communications cable conduit well, street lamp electricity pipeline fire well, all kinds of valve well, anti-corrosion engineering, minggou sheets, and according to the special needs of the user design and production.

[Common specifications:](#)

No.	Item	Description
1	Bearing Bar	25x3, 25x4, 25x4.5, 25x5, 30x3, 30x5, 30x5, 32x5, 40x5, 50x5, 65x5, 75x6, 75x10---100x10mm etc; I bar: 25x3, 30x5x3, 32x5x3, 40x5x3 etc US standard: 1"x3/16", 1 1/4"x3/16", 1/2"x3/16", 1"x1/4", 1 1/4"x1/4", 1/2"x1/4", 1"x1/8", 1 1/4"x1/8", 1/2"x1/8" etc
2	Bearing Bar Pitch	12.5, 15, 20, 23.85, 25, 30, 30.16, 34.3, 35, 38.1, 40, 41.25, 60, 80mm US standard: 19-w-4, 15-w-4, 11-w-4, 19-w-2, 15-w-2 etc.
3	Twisted Cross Bar Pitch	38.1, 50, 60, 76, 80, 100, 101.6, 120, 140, 150, 160, 180, 200, 240, 280, 320, 360, 400, 450, 480, 500, 550, 600, 650, 700, 750, 800, 850, 900, 950, 1000, 1050, 1100, 1150, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600, 1650, 1700, 1750, 1800, 1850, 1900, 1950, 2000, 2050, 2100, 2150, 2200, 2250, 2300, 2350, 2400, 2450, 2500, 2550, 2600, 2650, 2700, 2750, 2800, 2850, 2900, 2950, 3000, 3050, 3100, 3150, 3200, 3250, 3300, 3350, 3400, 3450, 3500, 3550, 3600, 3650, 3700, 3750, 3800, 3850, 3900, 3950, 4000, 4050, 4100, 4150, 4200, 4250, 4300, 4350, 4400, 4450, 4500, 4550, 4600, 4650, 4700, 4750, 4800, 4850, 4900, 4950, 5000, 5050, 5100, 5150, 5200, 5250, 5300, 5350, 5400, 5450, 5500, 5550, 5600, 5650, 5700, 5750, 5800, 5850, 5900, 5950, 6000, 6050, 6100, 6150, 6200, 6250, 6300, 6350, 6400, 6450, 6500, 6550, 6600, 6650, 6700, 6750, 6800, 6850, 6900, 6950, 7000, 7050, 7100, 7150, 7200, 7250, 7300, 7350, 7400, 7450, 7500, 7550, 7600, 7650, 7700, 7750, 7800, 7850, 7900, 7950, 8000, 8050, 8100, 8150, 8200, 8250, 8300, 8350, 8400, 8450, 8500, 8550, 8600, 8650, 8700, 8750, 8800, 8850, 8900, 8950, 9000, 9050, 9100, 9150, 9200, 9250, 9300, 9350, 9400, 9450, 9500, 9550, 9600, 9650, 9700, 9750, 9800, 9850, 9900, 9950, 10000 4" etc
4	Material Grade	ASTM A36, A1011, A569, Q235, S275, SS304, Mild steel & Low carbon steel
5	Surface Treatment	Black, self colour, hot dip galvanized, painted, spray coating
6	Grating Style	Plain / Smooth, Serrated /teeth, I bar, serrated I bar
7	Standard	China: YB/T 4001.1-2007, USA: ANSI/NAAMM(MBG531-88), UK: BS4592-1987, Australia: AS1669, Japan:JIS