

Q41F国标高平台法兰球阀

产品名称	Q41F国标高平台法兰球阀
公司名称	温州瑞通阀门有限公司
价格	165.00/只
规格参数	
公司地址	温州经济技术开发区滨海园区丁香路5幢4号
联系电话	0577 - 85888221 13626557497

产品详情

规格	
型号	q41f
公称通径	dn15~200mm (1/2"~8")
压力	pn1.6~6.4mpa, 150~300lb, 10k, 20k
适用温度	-10~150 ° c
适用介质	水、油、汽
	cf8(304): 适用于硝酸类
	cf8m(316):适用于醋酸类
技术规范	
设计标准	gb/t12237, api6d, bs5351
压力-温度额值	gb/t12224, ansi b 16.34
结构长度	gb/t12221, asmeb16.10, bs4460, din3202
连接法兰标准	gb9113, jb79, asme b16.5a, din2543~2546,
	bs4504, jisb2213~22
试验与检验标准	gb/t13927, iso5208, api598, api6d
材质	cf8(304), cf8m(316)
驱动方式	手动、电动、气动

pn mpa] dn mm]] e] b] c] d1]]] 1] h- h] h] h1] w] m] p] a]

1.6	15	130	95	65	45	-	14	2	-	4-14	48.0	79	135	9.0	9.0	6.0
	20	140	105	75	55	-	14	2	-	4-14	53.0	84	135	9.0	9.0	6.0
	25	150	115	85	65	-	14	2	-	4-14	54.0	95	170	11.0	11.0	6.0
	32	165	135	100	78	-	16	2	-	4-18	71.0	103	170	11.0	1.0	6.0
	40	180	145	110	85	-	16	3	-	4-18	76.0	111	200	14.0	14.0	7.0
	50	200	160	125	100	-	16	3	-	4-18	85.0	120	200	14.0	14.0	7.0
	65	220	180	145	120	-	18	3	-	4-18	104.0	153	300	17.0	17.0	9.0
	80	250	195	160	135	-	20	3	-	3-18	114.0	163	300	17.0	17.0	9.0
	100	280	215	180	155	-	20	3	-	3-18	140.0	182	400	22.0	22.0	h
	125	320	245	210	185	-	22	3	-	3-18	183.0	260	500	27.0	27.0	14.0
	150	360	280	240	210	-	24	3	-	3-23	202.0	280	300	27.0	27.0	14.0
	200	400	335	295	265	-	26	3	-	12-23	253.0	-	1100	27.0	27.0	14.0
2.5	15	130	95	65	45	-	16	2	-	4-14	48.0	79	135	9.0	9.0	6.0
	20	140	105	75	55	-	16	2	-	4-14	53.0	84	135	9.0	9.0	6.0
	25	150	115	85	65	-	16	2	-	4-14	54.0	95	170	11.0	11.0	6.0
	32	165	135	100	78	-	18	2	-	4-18	71.0	103	170	11.0	1.0	6.0
	40	180	145	110	85	-	18	2	-	4-18	76.0	111	200	14.0	14.0	7.0
	50	200	160	125	100	-	20	3	-	4-18	85.0	120	200	14.0	14.0	7.0
	65	220	180	145	120	-	22	3	-	3-18	104.0	153	300	17.0	17.0	9.0
	80	250	195	160	135	-	22	3	-	3-18	114.0	163	300	17.0	17.0	9.0
	100	280	230	190	160	-	24	3	-	3-23	140.0	182	400	22.0	22.0	h
	125	320	270	220	188	-	28	3	-	3-25	183.0	260	500	27.0	27.0	14.0
	150	360	300	250	218	-	30	3	-	3-25	202.0	280	300	27.0	27.0	14.0
	200	400	360	310	278	-	34	3	-	12-25	253.0	-	1100	27.0	27.0	14.0
4.0	15	130	95	65	45	40	16	2	4	4-14	48.0	79	135	9.0	9.0	6.0
	20	140	105	75	55	51	16	2	4	4-14	53.0	84	135	9.0	9.0	6.0
	25	150	115	85	65	58	16	2	4	4-14	54.0	95	170	11.0	11.0	6.0
	32	180	135	100	78	66	18	2	4	4-18	71.0	103	170	11.0	1.0	6.0
	40	200	145	110	85	76	18	3	4	4-18	76.0	111	200	14.0	14.0	7.0
	50	220	160	125	100	88	20	3	4	4-18	85.0	120	200	14.0	14.0	7.0
	65	250	180	145	120	110	22	3	4	3-18	104.0	153	300	17.0	17.0	9.0
	80	280	195	160	135	121	22	3	4	3-18	114.0	163	300	17.0	17.0	9.0
	100	320	230	190	160	150	24	3	4.5	3-23	140.0	182	400	22.0	22.0	h
	125	400	270	220	188	176	28	3	4.5	3-25	183.0	260	500	27.0	27.0	14.0
	150	400	300	250	218	204	30	3	4.5	3-25	202.0	280	300	27.0	27.0	14.0
	200	502	375	320	282	260	38	3	4.5	12-30	253.0	-	1100	27.0	27.0	14.0