

西门子代理商 6FX2007-1AD03

产品名称	西门子代理商 6FX2007-1AD03
公司名称	湖南西控自动化设备有限公司
价格	.00/件
规格参数	
公司地址	中国（湖南）自由贸易试验区长沙片区开元东路1306号开阳智能制造产业园（一期）4#栋301
联系电话	15344432716 15386422716

产品详情

6FX2007-1AD03

微型手持单元 6FX2007-1AD03 用于 SINUMERIK 配备 3.5m 螺旋状电缆 2 通道，紧急停止 2 通道，确认键，3 档位 带金属连接器 手轮带电磁制动机构

概述

该款便携式微型手持单元符合人体工学，具有坚固的金属接头，非常适合在车间里面调试和运行标准机床。

优势

轴的移动定位

易于对粗、中、细进给进行分级，便于快速、精确的增量定位

结构紧凑，坚固耐用

设计

急停功能是通过 4 线制连接在 2 个通道中实现的。

过 3 线制连接，在 2 个通道中实现 3 位置使能按钮

快速移动键和两个“±”键

一个用于在点动模式下移动轴的手轮

可以连接旋转开关以选择最多 5 个轴

适用于定制应用的 3 个功能键 – 用户可使用滑入式标签进行分配以进行标记

连接套件的接口（附件）

可选的直角插座可将电缆引出方向旋转 90°（附件）。角形接口仅能用于连接未预装配的连接套件。

使用集成式磁性夹或固定器（附件）进行安装

集成

微型手持单元可以用于：

SINUMERIK 828D

SINUMERIK 840D sl

SINUMERIK ONE

SINUMERIK MC

选型和订货数据（印刷版）

Description

Article No.

Mini handheld unit for SINUMERIK

3-step enabling buttonincl. magnetic clamps andconnecting cable with metal connector

Coiled connecting cableLength 2.1 m (6.89 ft),stretches to 3.5 m (11.48 ft)

6FX2007-1AD03

Straight cableLength 5 m (16.41 ft)

6FX2007-1AD13

Accessories

Connection kit formini handheld unit,non-assembled

Connection socket for self-assembly

Version with metal connector for connection to machine control panel without Industrial Ethernet, with terminator

6FX2006-1BG03

Connection kit for mini handheld unit, assembled

Connection socket wired up

Version with metal connector for connection to machine control panel with Industrial Ethernet, with terminator

6FX2006-1BG11

Connection kit for mini handheld unit, assembled

Version with metal connector for connection to machine control panel with PROFINET, with terminator for SINUMERIK 828D

6FX2006-1BG20

90 ° angle socket

For connection kit, non-assembled 6FX2006-1BG03 Metal version

6FX2006-1BG56

Holder

For mini handheld units 6FX2007-1AD.3 and electronic handwheel in housing 6FC9320-5DE02

6FX2006-1BG70

技术规范

Article number

6FX2007-1AD03

6FX2007-1AD13

Product brand name

SINUMERIK

SINUMERIK

product designation

Mini handheld unit

Mini handheld unit

product feature

With coiled cable

With straight cable

supply voltage at DC

V

24

24

supply voltage at DC

for handwheel

V

5

5

note

For emergency stop button, enabling buttons and switching signals

design of the interface

RS422

RS422

number of pulses per revolution maximum

100

100

transmission link of the handheld unit to the NCU/PCU maximum

m (ft)

25 (82.021)

25 (82.021)

note

When using the handwheel

When using the handwheel

Protection class without shaft input

IP65

IP65

environmental category acc. to IEC 60721-3-3

Condensation and icing excluded. Low air temperature 0 ° C (32 ° F).

Relative humidity at 25 ° C (77 ° F), during

storage

%

5 ... 95

5 ... 95

transport

%

5 ... 95

5 ... 95

operation

%

5 ... 95

5 ... 95

Ambient temperature, during

storage

° C (° F)

-20 ... +60 (-4 ... +140)

transport

° C (° F)

operation

° C (° F)

0 ... 55 (32 ... 131)

0 ... 55 (32 ... 131)

width

mm (in)

90 (3.54331)

90 (3.54331)

height

mm (in)

67 (2.6378)

67 (2.6378)

depth

mm (in)

180 (7.08661)

180 (7.08661)

note

With emergency stop button

With emergency stop button

net weight

kg (lb)

0.5 (1.10231)

0.5 (1.10231)

note

Without connecting cable

Without connecting cable

certificate of suitability

CE / UL

CE / UL