

美标矿用电缆高热塑性尼龙线THHN

产品名称	美标矿用电缆高热塑性尼龙线THHN
公司名称	上海埃线电线电缆咨询中心
价格	3.10/米
规格参数	品牌:埃因电缆 认证:美标认证 起订:300
公司地址	上海市奉贤区青村镇奉村路333号
联系电话	18121349647 18121349647

产品详情

美标矿用电缆高热塑性尼龙线THHN

应用

该电缆耐扭转、耐磨、温度范围广、耐UV和臭氧，专为风力涡轮设计。

标准

HD 22.12UL/CSA 22.2UL 758

结构

导体：IEC/EN 60228标准class 5柔软退火裸铜导体。绝缘：特殊高温交联E17橡胶（EPDM class 28）。特殊高温热固EPR可选。护套：高机械性能特殊交联EM7（CPE class 42）。特殊改善低温性能的热固CPE（-40）可选。

PVC-JZ/OZ-YCYPVC-JZ/OZ-CYPVC-JZ/OZ-YSYPVC-JZ/OZ 0,6/1kV schwarzPVC-JZ/OZ YCY 0,6/1kV schwarz2YSL(St)CY-J 0,6/1kV EMV, transparent2YSL(St)CYK-J 0,6/1kV EMV -UV, schwarz2YSL(St)CYK-J 0,6/1kV EMV-3 PLUS-UV, schwarz2YSL(St)CY-J 0,6/1kV EMV-3 PLUS, transparentH05VV5-FH05VVC4V5-KMultinorm H05VV5-F HAR/UL/CSAMultinorm-CY H05VVC4V5-K HAR/UL/CSA2-Norm (H)05VV5-F UL/CSA2-Norm-CY (H)05VVC4V5-K UL/CSAFLAME-JZ/OZ-H

FRNCFLAME-JZ/OZ-CH FRNCPUR (N)YMH11Y GRAU / GELBH05BQ-F, H07BQ-FHighflex LiFYESUY
Kupfer-ErdungsseilSOLAIRFLEX - S - 150H FRNC + UV 0,6/1 kV PV1-FSOLAIRFLEX - ECO - 120H FRNC +
UV 0,6/1 kVELITRONIC LIYYELITRONIC-CY LIYCYPAAARTRONIC LIYY (TP)PAAARTRONIC-CY LIYCY
(TP)PAAARTRONIC-CY-CY LIYCY-CY (TP)ELITRONIC LIYYELITRONIC-CY LIYCYELITRONIC
LIHHELITRONIC-CH LIHCHPAAARTRONIC-CH LIHCH (TP)ELITRONIC-OZ EB LIYY-OZELITRONIC-
OZ-CY EB LIYCY-OZELITRONIC LIYY UL/CSAELITRONIC-CY LIYCY UL/CSAPAAARTRONIC-CY LIYCY
(TP) UL/CSADATATRONIC-CY (TP) UL/CSADATEX-CY Li2YCY (TP)DATEX-PiMf-CY Li2YCY-PiMfJE-
Y(St)Y BdJE-LIYCY BdRD-Y(St)Y BdJE-H(St)H BdJE-H(St)H Bd FE180 E30-E90JE-LIHCH BdRD-H(St)H
BdTKF INDUCOM RE-2X(St)Y-flTKF INDUCOM RE-2X(St)Y-fl PiMfTKF INDUCOM RE-2X(St)YSWBY-
flTKF INDUCOM RE-2X(St)YSWBY-fl PIMFTKF INDUCOM RE-2X(St)YSWAY-flTKF INDUCOM
RE-2X(St)YSWAY-fl PIMFJ-Y(St)Y LgJ-2Y(St)Y St III BdJ-H(St)H BdA-2Y(L)2Y St III BdA-2YF(L)2Y St III
BdINTERBUS und INTERBUS HYBRID (RBC) / (INBC)INTERBUS und INTERBUS HYBRID (RBC) /
(INBC)MULTIBUS L2-D 100 - 120 MULTIBUS L2-D 100 - 120