

聚四氢呋喃醚PTMEG1000

产品名称	聚四氢呋喃醚PTMEG1000
公司名称	山东满堂红新材料有限公司
价格	32000.00/吨
规格参数	产地/产商:韩国台湾英威达 含量 :99.9 (%) 产品等级:优级品
公司地址	山东省济南市天桥区济南新材料交易中心办公楼 三层304-12号
联系电话	0531-88770911 18854153038

产品详情

产地/产商：韩国 台湾 英威达 含量 ：99.9 (%) 产品等级：优级品
CAS：电询 200公斤

规格型号：ptmeg 1000 和 ptmeg 2000

ptmeg 1800 和 ptmeg 3000

包装：200kg/桶

用于生产氨纶、聚氨酯弹性体、聚氨酯浆料等。

ptmeg	1000	1800	2000	3000
appearance	a white waxy solid, and may become transparent liquid over a room temperature			
average molecular weight	1000	1800	2000	3000
hydroxyl number	112	62	56	37
viscosity(cps,40)	310	1240	1445	4300
specific gravity(40/4)	0.975	0.974	0.974	0.97
refractive index	1.463	1.464	1.464	1.464
melting point(tm,)	24	28	32	35
glass transition point(tg,)	-76	-76	-76	

boiling point()	more than 204
flash pont(open cup,)	more than 260
alkalinity (m1n/1000hcl/30g)	from -3.0 to+1.0
iron (wt ppm)	less than 1
solubility	readily soluble in alcohols, esters and ketones, aromatic and chlorinated hydrocarbons. insoluble in aliphatic hydrocarbons and water. has a tendency to decrease its solubility as molecular weight increase.
hygroscopicity	these ptmeg are all hygroscopic. at room temperature, ptmeg can absorb up to 2wt% water depending on the molecular weight

a2. korea ptg ' s ptmeg sales specifications

product	ptmeg1000	ptmeg1800	ptmeg2000	ptmeg3000
molecular weight (g/mol)	1000 ± 50	1800 ± 50	2000 ± 50	3000 ± 50
hydroxyl number (mgkoh/g)	106.9-118.1	60.6-64.1	54.7-57.5	36.2-38.7
color	max. 30 apha			
acid number	max. 0.05 mgkoh/g			
water	max. 200 wt ppm			
peroxide	max. 10 wt ppm as			
volatiles	max. 0.1 wt%			
stabilizer	220 ± 50 wt ppm			