



jk- 2/20	1	2	1.5	60	60	24.5	290	610	950	5.0/3.7	348/256	980/730	79
jk- 2/30	1	2	1.5	60	60	24.5	290	610	950	3.3/2.5	215/180	980/730	79
jk-2 × 1.8/20	1	2	1.8	60	60	24.5	330	720	1125	5.0/3.7	348/256	980/730	79
jk-2 × 1.8/30	1	2	1.8	60	60	24.5	330	720	1125	3.3/2.5	215/180	980/730	79
2jk- 2/11.5	2	2	1	60	40	24.5	170	380	600	6.64/5.32	300/240	730/585	82
2jk- 2/20	2	2	1	60	40	24.5	170	380	600	5.12/3.81	215/155	980/730	82
2jk- 2/30	2	2	1	60	40	24.5	170	380	600	3.41/2.54	155/110	980/730	82
2jk-2 × 1.25/11.5	2	2	1.25	60	40	24.5	235	505	810	6.7/5.32	315/240	736/585	2575
2jk-2 × 1.25/20	2	2	1.25	60	40	24.5	235	505	810	5.12/3.81	215/155	980/730	2575
2jk-2 × 1.25/30	2	2	1.25	60	40	24.5	235	505	810	3.41/2.54	155/110	980/730	2575
2jk-2 × 1.5/11.5	2	2	1.5	60	40	24.5	320	680	1040	6.64/5.32	300/240	730/585	2658
2jk-2 × 1.5/20	2	2	1.5	60	40	24.5	320	680	1040	5.12/3.81	215/155	980/730	2658
2jk-2 × 1.5/30	2	2	1.5	60	40	24.5	320	680	1040	3.14/2.54	155/110	980/730	2658
jk- 2.5/20	1	2.5	2.0	90	90	31	400	810	1290	4.7/3.8	470/394	730/580	323
jk- 2.5/30	1	2.5	2.0	90	90	31	400	810	1290	3.2/2.5	332/260	720/580	323

jk-2.5 × 2.2/20	1	2.5	2.2	90	90	31	454	933	1454	4.7/3.8	470/394	730/580	10.5 × 9.84 × 2.83	3507
jk-2.5 × 2.2/30	1	2.5	2.2	90	90	31	454	933	1454	3.2/2.5	332/260	720/580	10.5 × 9.84 × 2.83	3507
jk-2.5 × 2.3/20	1	2.5	2.3	90	90	31	478	1023	1581	4.7/3.8	470/394	730/580	10.6 × 9.84 × 2.83	3544
jk-2.5 × 2.3/30	1	2.5	2.3	90	90	31	478	1023	1581	3.2/2.5	332/260	720/580	10.6 × 9.84 × 2.83	3544
jk-2.5 × 2.5/20	1	2.5	2.5	60	60	24.5	521	1088	1690	4.7	470	730	10.8 × 9.84 × 2.83	3686

型号	卷筒						钢绳				电动机		
	数量	直径 m	宽度 m	最大静张力 kn	最大静张力差 kn	直径 mm	容绳量m			速度 m/s	功率kw	转速 rpm	
							一层缠绕	二层缠绕	三层缠绕				
2jk-2.5/11.5	2	2.5	1.2	90	55	31	220	500	790	5.5/6.6/8.2	330/400/570	485/580/730	11.2
2jk-2.5/20	2	2.5	1.2	90	55	31	220	500	790	3.8/4.7	260/300	580/730	11.2
2jk-2.5/30	2	2.5	1.2	90	55	31	220	500	790	2.5/3.2	160/200	580/730	11.2
2jk-2.5 × 1.5/11.5	2	2.5	1.5	90	55	31	290	640	1000	6.6/8.2	400/570	588/730	11.8
2jk-2.5 ×		2.5	1.5	90	55	31	290	640	1000	3.8/4.7	260/300	580/730	11.8

1.5/20	2													
2jk-2.5 × 1.5/30	2	2.5	1.5	90	55	31	290	640	1000	2.5/3.2	160/200	580/730	11.8	
2jk-2.5 × 1.35/11.5	2	2.5	1.35	90	55	31	250	570	900	6.6/8.2	400/570	580/730	11.5	
2jk-2.5 × 1.35/20	2	2.5	1.35	90	55	31	250	570	900	3.8/4.7	260/300	580/730	11.5	
2jk-2.5 × 1.35/30	2	2.5	1.35	90	55	31	250	570	900	2.5/3.2	160/200	580/730	11.5	
jk-3 × 2.2/20	1	3	2.2	135	135	36	485	966	1513	5.73/4.56/3.81	794/631/528	730/580/485	13	
2jk-3/11.5	2	3	1.5	130	80	37	282	596	955	6.62/7.92/9.97	565/675/850	485/580/730	13.7	
2jk-3/20	2	3	1.5	130	80	37	282	596	955	4.56/5.73	388/489	580/730	13.7	
2jk-3/30	2	3	1.5	130	80	37	282	596	955	3.04/3.82	259/326	580/730	13.7	
2jk-3 × 1.8/11.5	2	3	1.8	130	80	37	362	770	1217	9.97/7.92/6.62	850/657/565	730/580/485	14	
2jk-3 × 1.8/20	2	3	1.8	130	80	37	362	770	1217	5.73/4.56	489/388	580/730	14	
2jk-3 × 1.8/30	2	3	1.8	130	80	37	362	770	1217	3.04/3.82	259/326	580/730	14	
jk-3.5 × 2.5/30	1	3.5	2.5	170	170	38	602	1229		3.35	610	550		
2jk-3.5/11.5	2	3.5	1.7	170	115	40	349	746		7.93/9.49/11.94	973/1163/1463	485/580/730	15	
2jk-3.5/20		3.5	1.7	170	115	40	349	746		4.44/5.31/6.69	545/651/820	485/580/730	15	

	2												
2jk-3.5/30	2	3.5	1.7	170	115	40	349	746		4		230	
2jk-4 × 2.1/30	2	4	2.1	245	160	50				891		3.45	560

型号	卷筒				钢绳最大静张力kn	钢绳最大静张力差kn	容绳量			钢绳	减速比	钢绳速度m/s	
	个数	直径m	宽度m	一层缠绕m			二层缠绕m	三层缠绕m	最大直径mm				功率kw
jkb-2 × 1.5	1	2	1.5	60	60	290	610	950	24.5	20	3.87	250	
											5.12	315	
											30	2.58	185
												3.14	200
jkb-2 × 1.8	1	2	1.8	60	60	330	720	1125	24.5	20	3.87	250	
											5.12	315	
											30	2.58	185
												3.14	200
2jkb-2 × 1	2	2	1	60	40	170	380	600	24.5	20	3.81	155	
											5.12	215	
											30	2.54	110

												3.14	155
2jkb- 2 × 1.25	2	2	1.25	60	40	235	505	810	24.5	20	3.81	155	
											5.12	215	
										30	2.54	110	
											3.14	155	
2jkb- 2 × 1.5	2	2	1.5	60	40	320	680	1040	24.5	20	3.81	155	
											5.12	215	
										30	2.54	110	
											3.14	155	
jkb- 2.5 × 2.0	1	2.5	2.0	90	90	400	810	1290	31	20	4.7	470	
											3.8	394	
										30	3.2	332	
											2.5	260	
jkb- 2.5 × 2.3	1	2.5	2.3	90	90	478	1023	1581	31	20	4.7	470	
											3.8	394	
										30	3.2	332	
											2.5	260	
2jkb- 2.5 × 1.2	2	2.5	1.2	90	55	220	500	790	31	20	3.8	260	
											4.7	300	

										30	2.5	160	
											3.2	200	
2jkb- 2.5 × 1.5	2	2.5	1.5	90	55	290	640	1000	31	20	3.8	260	
											4.7	300	
										30	2.5	160	
											3.2	200	