

仪表仪器低温填充油 -60 ° C up to 200 ° C

| | |
|------|---------------------------------|
| 产品名称 | 仪表仪器低温填充油 -60 ° C up to 200 ° C |
| 公司名称 | 上海恩莱保贸易有限公司 |
| 价格 | .00/件 |
| 规格参数 | ELB:ELB |
| 公司地址 | 上海市松江区金高路2388号813室 |
| 联系电话 | 86-021-20228098 13391171050 |

产品详情

低温合成硅油，广泛使用于仪表填充is a heat transfer fluid based on polydimethylsiloxane that is used in baths for a temperature range of -60 ° C to 120 ° C and in other open systems with contact with the atmosphere as well as closed systems without an influx of oxygen at temperatures of -60 ° C up to 200 ° C. The maximum permissible film temperature is 220 ° C.低温冷却导热液

典型数据：

Density 25 ° C:

904 kg/m³

Kin. viscosity 40 ° C:

1,50 mm²/s

Pour Point:

<-120 ° C

Minimal operating temperature:

-80 ° C

Bulk temperature max.:

270 ° C

Film temperature max.:

290 ° C

Boiling Point:

>225 ° C

Flash Point:

>82 ° C

Water hazard classification:

1

Approval :

-