

# 16B温度过程控制仪

|      |                            |
|------|----------------------------|
| 产品名称 | 16B温度过程控制仪                 |
| 公司名称 | 合肥万康检测仪器有限公司               |
| 价格   | 820.00/台                   |
| 规格参数 |                            |
| 公司地址 | 安徽省合肥市濉溪路与张洼路交口新海世纪大厦B1504 |
| 联系电话 | 13855103484                |

## 产品详情

双路控制输出，rs485通讯，通用输入

输入: thermocouple, rtd, dc voltages or dc current.

显示: two 4-digit, 7 segment .25" h (6.35 mm) led's. pv: red; sv: green.

精度:  $\pm 0.25\%$  span,  $\pm 1$  least significant digit.

电源: 100 to 240 vac, 50/60 hz.

功耗: 5 va max.

操作温度: 32 to 122 ° f (0 to 50 ° c).

记忆: 永久记忆

输出参数: relay: spst, 5 a @ 250 vac resistive; voltage pulse: 14 v, 10% to -20% (max 40 ma); current: 4 to 20 ma.

通讯: rs-485 modbus® a-5-11/rtu communication protocol.

重量: 4 oz (114 g).

认证: ce, ul, cul, rohs.

前面板封装: nema 4x (ip66).

| 型号     | 特性   |
|--------|--|
| 16b-22 | 1/16 din temperature/process controller, (2) voltage pulse outputs.                          |
| 16b-23 | 1/16 din temperature/process controller, voltage pulse output 1 and relay output 2.          |
| 16b-32 | 1/16 din temperature/process controller, relay output 1 and voltage pulse output 2.          |
| 16b-33 | 1/16 din temperature/process controller, relay outputs 1 and 2.                              |
| 16b-52 | 1/16 din temperature/process controller, current output 1 and voltage pulse output 2.        |
| 16b-53 | 1/16 din temperature/process controller, current output 1 and relay output 2.                |
| 16b-62 | 1/16 din temperature/process controller, linear voltage output 1 and voltage pulse output 2. |
| 16b-63 | 1/16 din temperature/process controller, linear voltage output 1 and relay output 2.         |