

## 30%玻纤增强 PBT 美国杜邦 SK605 BK851 挤出级 注塑级 耐低温

产品名称	30%玻纤增强 PBT 美国杜邦 SK605 BK851 挤出级 注塑级 耐低温
公司名称	京冀（广州）新材料有限公司
价格	21.00/千克
规格参数	PBT:挤出级 SK605:耐低温 美国杜邦:注塑级
公司地址	广州市南沙区丰泽东路106号（自编1号楼）X130 1-E014087（注册地址）
联系电话	18938547875 18938547875

### 产品详情

PBT/美国杜邦/S660FR 阻燃级

PBT篇

特性：PBT机械性能优良，摩擦系数小、吸水率低；电气性能优良，尺寸稳定性良好，耐药品性、耐油性，应用：电子电器、汽车工业、机械零部件等。

供应美国杜邦PBT S600 高粘度 高韧性供应美国杜邦PBT SK602 添加15%玻璃纤维供应美国杜邦PBT SK603 添加20%玻璃纤维供应美国杜邦PBT SK605 添加30%玻璃纤维供应美国杜邦PBT SK652FR 添加15%玻璃纤维 阻燃V0

PBT/DuPont/S660FR

PBT section

: PBT , , ; elektointestinal performance;

Applications: Electronics, automotive industry, mechanical component etc.

Supporte PBT 600, USA;

Supported DuPont PBT SK602 with 15% glass fiber

undo-type

Supported DuPont PBT SK605 with 30% glass fiber

Supported DuPont PBT SK652FR with 15% glass fiber V0 United States.

PBT ,

, droga-resistans, ,

Electronics, automotive industry, mechanical components, etc.

Supply DuPont PBT S600 with high viscosity and high toughness in the United States

Supply DuPont PBT SK602 with 15% glass fiber added

Supply DuPont PBT SK603 with 20% glass fiber added

Supply DuPont PBT SK605 with 30% glass fiber added

Supply DuPont PBT SK652FR with 15% glass fiber flame retardant V0 in the United States

Taqsim PBT

Karatteristii: PBT gandu proprjetajiet mekkanii eellenti, koeffijent ta' frizzjoni baxx, u assorbiment baxx tal-ilma; Prestazzjoni elettrika eellenti,

Stabbiltà dimensjonali tajba, reistenza gall-mediina, reistenza ga-ejt,

Applikazzjonijiet: Elettronika, industrija tal-karozzi, komponenti mekkanii, e.

Provvista DuPont PBT S600 b' viskoit à golja u b' ebusija golja fl-Istati Uniti

Provvista DuPont PBT SK602 b' 15% fibra tal-ie mijuda

Provvista DuPont PBT SK603 b' 20% fibra tal-ie mijuda

Provvista DuPont PBT SK605 b' 30% fibra tal-ie mijuda

Provvista DuPont PBT SK652FR b' 15% retardant tal-fjamma tal-fibra tal-ie V0 fl-Istati Uniti