MOLEX 莫仕连接器 42819-2212 深圳华强赛格电子市场特价

产品名称	MOLEX 莫仕连接器 42819-2212 深圳华强赛格电子市场特价
公司名称	深圳市华联科创科技有限公司
价格	2.00/PCS
规格参数	
公司地址	深圳市福田区新华强电子市场4F005
联系电话	86-075582534480 13828767900

产品详情

是否提供加工定制：	是	品牌：	Molex/莫莱克斯
型号：	42819-2212	应用范围：	PCB
种类：	板对线	接口类型：	1394
支持卡数：	单卡	读卡类型：	CF
形状：	条形	制作工艺：	注塑
特性：	阻火/阻燃	工作频率：	低频
接触件材质：	铜	绝缘体材质：	PA
芯数：	多芯	针数：	多针
线长：	11（mm）		

part detailcollapse all
general
statusactive
categorypcb headers
series42819
applicationpower, wire-to-board
overviewmini-fit sr.™
product namemini-fit sr.™

physical
breakawayno
circuits (loaded)2
circuits (maximum)2
color - resinblack
durability (mating cycles max)30
first mate / last breakno

flammability94v-0
glow-wire compliantno
guide to mating partno
keying to mating partnone
lock to mating partyes
material - metalbrass
material - plating matingtin
material - plating terminationtin
material - resinhigh temperature thermoplastic
number of rows1
orientationvertical
pc tail length3.50mm
pcb locatoryes
pcb retentionyes
pcb thickness - recommended1.60mm
packaging typetray
pitch - mating interface10.00mm
pitch - termination interface10.00mm
plating min - mating2.540 µ m
plating min - termination2.540 µ m
polarized to mating partyes
polarized to pcbyes
shroudedfully
stackableno
surface mount compatible (smc)no
temperature range - operating-40 ° c to +105 ° c
termination interface: stylethrough hole

electrical
(please review the product specification for specific details.)
current - maximum50a
voltage - maximum600v

agency certification
csalr19980
tuvr72081037
ule29179

solder process data
duration at max. process temperature (seconds)3
lead-free process capabilitywave capable (th only)
max. cycles at max. process temperature1

process temperature max. c265

material info

reference - drawing numbers

product specificationps-42815-001, rps-42815-001, rps-42815-010, rps-42815-011, rps-42815-012, rps-42815-013, rps-42815
rps-42815-015
sales drawingsda-42819-0002
test summaryts-42815-001