

# 高抗冲 ABS 台湾奇美 PA-707 通用级 高刚性

产品名称	高抗冲 ABS 台湾奇美 PA-707 通用级 高刚性
公司名称	京冀（广州）新材料有限公司
价格	14.00/千克
规格参数	ABS:高抗冲 PA-707:高刚性 台湾奇美:通用级
公司地址	广州市南沙区丰泽东路106号（自编1号楼）X1301-E014087（注册地址）
联系电话	18938547875 18938547875

## 产品详情

ABS/PA-765 1/16" UL94V-0 1/10" 5VA 5.2g/10min, 1.2g/cm<sup>3</sup>, 20, 38MPa, 15%?

ABS/PA-765A 1/12" UL94V-0 1/10" 5VA 4.8g/10min, 1.17/cm<sup>3</sup>, 21, 39MPa, 15%?

ABS/PA-765B 1/10" UL94V-0 1/16" V2 1/8" 5VA 2.6g/10min, 1.16g/cm<sup>3</sup>, 24, 39MPa, 25%

ABS/PA-777B 6.7g/10min, 1.03g/cm<sup>3</sup>, 23, 4

2MPa?????:15%?

Propiedat ABS/PA-765: 1/16 "UL94V-0, 1/10" 5VA, alto liquidity. Importante parametri: Melt flow rate: 5.2g/10min, density: 1.2g/cm<sup>3</sup>, notch impact strength: 20, tensile strength: 38MPa, elongation at break: 15%.

ABS/PA-765A propiedat: 1/12 "UL94V-0, 1/10" 5VA, alto likviditate. Importante parametri: melt flow rate: 4.8g/10min, density: 1.17/cm<sup>3</sup>, notch impact strength: 21, tensile strength: 39MPa, elongation at break: 15%.

ABS/PA-765B karakteristik note: 1/10 "UL94V-0, 1/16" V2, 1/8 "5VA, medio impact strength. Importante parametri: Melt flow rate: 2.6g/10min, density: 1.16g/cm<sup>3</sup>, notch impact strength: 24, tensile strength: 39MPa, elongation at break: 25%

Characteristics ABS/PA-777B Importante parametri: Melt flow rate: 6.7g/10min, density: 1.03g/cm<sup>3</sup>, notch impact strength: 23, tensile strength: 42MPa, elongation at break: 15%.

nya ana ne Tokyo-765 Anapaasa sakyar: 1 ne 16 kenaduru 94w- 0, 1 ne 10 daw5Kensa, fomowoyMillwotu. sm antbo anidsa: Seedi y euro: 5.2Wane 10wma, w: 1.2Wane esoSus3, tia mmara bio mfin: 20, nguwofiri mfin: 38orbr, ton NE odada be: 15%.

nya ana ne Tokyo-765aboAnapaasa sakyar: 1 ne 12 kenaduru 94w- 0, 1 ne 10 daw5Kensa, fomowoyMillwotu. sm antbo anidsa: baabi say euro: 4.8Wane 10wma, w: 1.17 ne esoSus3, tia mmara bio mfin: 21, nguwofiri mfin: 39orbr, ton NE odada be: 15%.