

# 日本大金 NEOFLOON PFA AP-230SH 管材 板材 耐应力开裂

产品名称	日本大金 NEOFLOON PFA AP-230SH 管材 板材 耐应力开裂
公司名称	天津市星云新材料有限公司
价格	380.00/千克
规格参数	品牌:日本大金 规格:25公斤/包 产地:大金
公司地址	天津市东丽区航双路与津滨快速路交口处东北侧 航空商务中心2#-1,2-201(二层2057室)
联系电话	18622344552 18622344552

## 产品详情

**NEOFLOON PFA AP-230SH (PFA)**  
[DAIKIN INDUSTRIES Ltd.](#)

NEOFLOON PFA AP-202 is an ultra-high flowability fluororesin. It is suitable for extrusion molding of fine and thin wall electric wire. Introduction

AP-202 is a copolymer of tetrafluoroethylene and perfluoroalkyl vinyl ether.

Good melt flowability while maintaining excellent properties of PTFE. It can be melt-molded as a thermoplastic resin by injection molding and extrusion molding.

Suitable for extrusion molding of extremely fine electric wires. It is also used for electric wires of personal computers and mobile phones.

Excellent chemical resistance which is not affected by most of the chemicals.

It retains flexibility without losing toughness under the environment from cryogenic to high temperature.

Low dielectric constant and dielectric loss tangent in a wide range of temperature and frequency.

It shows high electrical resistance and dielectric strength.

Nonflammable like POLYFLON PTFE and NEOFLOON FEP. outside for a long time.

Non-stickiness. It shows excellent releasability and water repellency / oil repellency.

与典型值比较 -

[Upgrade to compare!](#)

单位: SI

总览

材料状态

资料 1

搜索 UL 黄卡

已商用：当前有效

[Technical Datasheet \(English\)](#)

[DAIKIN INDUSTRIES, Ltd.](#)

[Neoflon](#)

供货地区

北美洲

非洲和中东

拉丁美洲

欧洲

亚太地区