

PZ673W-10NR DN150气动高温排渣阀主要外形和连接尺寸：

| DN | PN(Mpa) | L | D | D1 | D2 | H | N-M | D0 | b |
|-----|---------|----|-----|-----|-----|------|--------|-----|----|
| 50 | 1.0 | 43 | 165 | 125 | 100 | 285 | 4-M16 | 180 | 12 |
| 65 | | 46 | 185 | 145 | 120 | 295 | 4-M16 | 180 | 12 |
| 80 | | 46 | 200 | 160 | 135 | 315 | 8-M16 | 220 | 12 |
| 100 | | 52 | 220 | 180 | 155 | 365 | 8-M16 | 220 | 12 |
| 125 | | 56 | 250 | 210 | 185 | 400 | 8-M16 | 230 | 12 |
| 150 | | 56 | 285 | 240 | 210 | 475 | 8-M20 | 280 | 14 |
| 200 | | 60 | 340 | 295 | 265 | 540 | 12-M20 | 360 | 14 |
| 250 | | 68 | 405 | 355 | 320 | 630 | 12-M24 | 360 | 16 |
| 300 | | 78 | 460 | 410 | 375 | 780 | 12-M24 | 400 | 16 |
| 350 | | 90 | 520 | 470 | 435 | 885 | 16-M24 | 400 | 16 |
| 400 | | 90 | 580 | 525 | 485 | 990 | 16-M27 | 400 | 18 |
| 450 | | 90 | 640 | 585 | 545 | 1100 | 20-M27 | 530 | 18 |