

友联CH-DL单头立式膏体灌装机

产品名称	友联CH-DL单头立式膏体灌装机
公司名称	温州市友联机械制造有限公司
价格	4900.00/台
规格参数	
公司地址	浙江省温州市瓯海娄桥创新路10号
联系电话	0086-057786139198 18968809951

产品详情

ch-dl单头立式膏体灌装机

产品特点：

本系列膏体定量灌装机是在本公司灌装机系列的基础上，参照国外先进灌装机技术进行改造和创新的产品，其结构更加简单合理，精确度高，操作更加简便。该设备采用特殊转阀控制进料和计量，适用于医药、日化、食品、农药及特殊行业，是对高粘度、膏体、浓酱带颗粒、液体进行灌装的理想设备。该系列为半自动双活塞式膏体灌装机，设计合理，机型小巧，操作方便，气动部分均采用台湾airtac、shako的气动元件。物料接触部分均采用304不锈钢材料制成，符合gmp要求。

有灌装量调节手柄、灌装速度可任意调节，灌装精度高。

灌装闷头采用防滴漏、防拉丝及升降灌装装置。料斗可加装可调速电机搅拌和保温料斗。

可根据客户要求定做，比如气缸品牌、不锈钢材料、密封圈材料等。

技术参数：

电源	220/110v50/60hz
气压	0 . 4-0 . 6mpa
灌装速度	5-30瓶/分

灌装精度	± 1%
可选机型	5-100ml 110-280ml 120-500ml 100-1000ml 500-2800ml 1000-5000ml

ch-dl one head ointment filling machine (floor type)

introduction :

the model g11gd is a product innovated and upgraded on the basis of this companys series products and introduced foreign advanced filling machine technology.. the product is simple and reasonable in design, high in accuracy and easy in operation.

the equipment uses special rotating valve to control material-feeding and measurement, especially suits for the filling of high-viscosity material(e.g.crude oil, asphalt, paint,emulsion etc.)

suitable for filling various kinds of highly viscous fluid in the industries of pharmaceuticals, daily chemicals, foodstuffs, cosmetics, pesticide and special trades. with no need for power supply, the machine is safe and with the personalized design, can meet the modern enterprises requirements.

this machine is the semi-automatic double piston liquid filling machine, working under the state without electricity, it is safer to operate.

this machine reasonable in design, smart in model, easy to operate, the pneumatic part adopts the pneumatic components of taiwans airtac、 shako.

the part contacting materials is made of 316l stainless steel.

with adjustment handle of filling volume, the filling speed can be adjusted at will, with high filling accuracy.

filling head adopts anti-leakage, anti-pull and with diving filling device.

according to customer requirements, such as brand, stainless steel materials, cylinder seal materials etc.

technical parameter :

power supply	220/110v50/60hz
--------------	-----------------

air pressure	0 . 4-0 . 6mpa
filling speed	5-30bottles/min
filling accuracy	$\pm 1\%$
filling volumes range	5-100ml 10-280ml 20-500ml 100-1000ml 500-2800ml 1000-5000ml