

# 0805插件工字型电感RL855-680K-RC大电流大功率矿显卡电源DC-DC转换器电脑家用电器服务器主板电感

产品名称	0805插件工字型电感RL855-680K-RC大电流大功率矿显卡电源DC-DC转换器电脑家用电器服务器主板电感
公司名称	深圳市好东方新能源环保有限公司
价格	1.68/个
规格参数	品牌:H-EAST/好东方 产地/库存:深圳/现货 型号:RL855-680K-RC
公司地址	深圳市宝安区沙井街道新和路衙边第三工业区
联系电话	18319053074 18319053074

## 产品详情

替代Bourns型号	电感值(μH)	DCR Typ(mΩ)	饱和电流(A)	温升电流(A)	工作温度(°C)	长(mm)	宽(mm)
RL855-100M-RC	10	46	4.59	3.12	-40~125	8.3	8.3
RL855-101K-RC	100	375	1.45	1.04	-40~125	8.3	8.3
RL855-102K-RC	1000	3610	0.45	0.35	-40~125	8.3	8.3
RL855-120M-RC	12	53	4.19	2.87	-40~125	8.3	8.3
RL855-121K-RC	120	452	1.32	0.99	-40~125	8.3	8.3
RL855-150M-RC	15	70.2	3.7	2.52	-40~125	8.3	8.3
RL855-151K-RC	150	568	1.18	0.89	-40~125	8.3	8.3
RL855-180M-RC	18	78.9	3.4	2.42	-40~125	8.3	8.3
RL855-181K-RC	180	701	1.08	0.82	-40~125	8.3	8.3
RL855-220K-RC	22	94	3.09	2.19	-40~125	8.3	8.3
RL855-221K-RC	220	822	1	0.73	-40~125	8.3	8.3
RL855-222K-RC	2200	7800	0.32	0.22	-40~125	8.3	8.3
RL855-270K-RC	27	112	2.79	2	-40~125	8.3	8.3
RL855-271K-RC	270	1056	0.88	0.65	-40~125	8.3	8.3
RL855-330K-RC	33	129	2.52	1.86	-40~125	8.3	8.3
RL855-331K-RC	330	1205	0.8	0.6	-40~125	8.3	8.3
RL855-390K-RC	39	151	2.32	1.72	-40~125	8.3	8.3
RL855-391K-RC	390	1380	0.73	0.55	-40~125	8.3	8.3
RL855-470K-RC	47	203	2.12	1.48	-40~125	8.3	8.3
RL855-471K-RC	470	1590	0.7	0.52	-40~125	8.3	8.3
RL855-472K-RC	4700	17470	0.21	0.16	-40~125	8.3	8.3
RL855-560K-RC	56	228	1.94	1.4	-40~125	8.3	8.3

RL855-561K-RC	560	2389	0.61	0.43	-40~125	8.3	8.3
RL855-680K-RC	68	268	1.76	1.28	-40~125	8.3	8.3
SRP1770C-8R2M	8.2	7.75	20	16	-40~125	17.8	17
SRP4020TA-100Y	10	238	2.2	1.8	-40~125	4.4	4.2
SRP4020TA-1R0Y	1	20.9	9	6.2	-40~125	4.4	4.2
SRP4020TA-1R2Y	1.2	21	7	6.2	-40~125	4.4	4.2
SRP4020TA-1R5Y	1.5	39	6	4.5	-40~125	4.4	4.2
SRP4020TA-2R2Y	2.2	50.5	5	4	-40~125	4.4	4.2
	1	11.5	8.4	10	-40~125	4.3	4.3
SRP4020FA-1R0M							
SRP4020FA-R47M	0.47	5.8	12.1	13.5	-40~125	4.3	4.3
SRP4020FA-R68M	0.68	8.5	10.5	12	-40~125	4.3	4.3
SRP4020FA-R82M	0.82	9.7	9	11.6	-40~125	4.3	4.3
SRP4020TA-1R0M	1	8.9	9.5	10.2	-40~125	4.3	4.3
SRP4020TA-1R5M	1.5	11	8.3	9	-40~125	4.3	4.3
SRP4020TA-2R2M	2.2	17.1	6.5	8.5	-40~125	4.3	4.3
SRP4012TA-100M	10	250	1.75	1.75	-40~125	4.4	4.2
SRP4012TA-1R0M	1	31.1	5.5	5	-40~125	4.4	4.2
SRP4012TA-2R2M	2.2	53.5	4.2	4.2	-40~125	4.4	4.2
SRP4012TA-8R2M	8.2	196	1.8	1.8	-40~125	4.4	4.2
SRP4012TA-R10Y	0.1	4.3	18	15	-40~125	4.4	4.2
SRP4012TA-R22M	0.22	8.9	12	10.5	-40~125	4.4	4.2
SRP4020TA-100M	10	110	2.5	2.5	-40~125	4.4	4.2
SRP4020TA-150M	15	217	2.2	2.2	-40~125	4.4	4.2