

型号 model	流量 flow	马达 motor	净重 dry weight	运行重 量 wet weight	入水/出 水 water inlet water outlet	满水/排 水 overf low/drai n	塔体 tower	壳身 casing	水盆 water basin	出/入水 高度 water inlet water outlet	风扇直 径 exhaust fan	水盆直 径 water basin	基 底
	m3/h	kw	kg	kg	wi/wo	of/dri n	th	ch	wh	in/oh	ed	wd	
8t	6.2	0.18	42	180	40/40	25/25	1550	875	335	180/270	525	945	
10t	7.8	0.18	46	190	40/40	25/25	1700	1025	335	180/270	600	945	
15t	12	0.37	54	290	50/50	25/25	1585	895	350	190/280	600	1195	
20t	16	0.55	67	300	50/50	25/25	1760	1070	350	190/280	730	1195	
25t	20	0.75	98	500	80/80	25/25	2000	1215	360	115/175	730	1400	
30t	23	0.75	116	530	80/80	25/25	1885	1110	350	115/175	730	1650	
40t	31	1.5	130	550	80/80	25/25	1975	1180	350	115/175	890	1650	
50t	39	1.5	190	975	80/80	25/25	2035	1230	360	125/230	890	1830	
60t	47	1.5	240	1250	100/100	25/25	2225	1230	400	200/295	1150	2145	
80t	63	1.5	260	1280	100/100	25/25	2305	1310	400	200/295	1150	2145	
100t	78	2.25	500	1600	125/125	50/50	2690	1595	450	230/300	1450	2900	
125t	98	2.25	540	1640	125/125	50/50	2875	1780	450	230/300	1450	2900	
150t	117	2.25	580	1680	150/150	50/50	2875	1780	450	230/300	1450	2900	
175t	137	3.75	860	1960	150/150	50/50	3515	1965	850	245/850	1750	3310	

200t	156	3.75	880	1980	150/150	50/50	3515	1965	850	245/850	1750	3310
225t	176	5.5	1050	2770	200/200	80/80	4170	2060	900	280/900	2135	4120
250t	195	5.5	1080	2800	200/200	80/80	4170	2060	900	280/900	2135	4120
300t	234	7.5	1760	3930	200/200	80/80	4360	2160	900	280/900	2440	4730
350t	237	7.5	1800	3970	200/200	80/80	4360	2160	900	280/900	2440	4730
400t	312	11	2840	5740	200/200	80/80	4550	2180	900	280/900	2745	5600
500t	329	11	2900	5800	250/250	100/100	4550	2180	900	280/900	2745	5600
600t	468	15	3950	9350	250/250	100/100	5310	2430	1020	340/1020	3400	6600
700t	547	18.5	4050	9450	250/250	100/100	5510	2630	1020	340/1020	3400	6600
800t	626	22	4700	11900	300/300	100/100	5660	2680	1020	340/1020	3700	7600
1000t	781	22	4900	12100	300/300	100/100	5860	2880	1020	340/1020	3700	7600

以上规格如有变更，恕不另行通知，特殊规格可另行设计制造。special design upon request.

备注：设计工况参数：进水温度-t1=37 出水温度-t2=32 湿球温度-wbt=27 水温降 ts=5 ° 大气压力-p=99400pa

鑫邦冷却塔广泛用于：冷冻、空调、电力、轻纺、化工等行业。