

深喉气动冲床 单臂气动冲床 C型气动冲床

产品名称	深喉气动冲床 单臂气动冲床 C型气动冲床
公司名称	玉环方博机械有限公司
价格	.00/台
规格参数	
公司地址	浙江台州玉环汽摩园工业区
联系电话	0576-87216855 13967655592

产品详情

2吨大型气动冲床，深喉式气动压装机，气动冲床比较卫生，干净！采用先进的光电保护技术，可以实现安全性能的大幅提升，电脑计数与程序的配合，可以实现无人值守的加工流程，大大提升了工作的效率，降低生产的成本。可根据用户要求，另配置进口plc、光栅保护以及人机界面（触摸屏）等先进元器件。对于客户的特殊要求，我们可以特别设计生产，最大限度的满足客户生产工艺要求。有意者请致电：13967655592

0576-87216855，何女士。或者发送邮件至fangbo.cn@163.com或者登陆我司官网www.fangbo.cn.com

fbq-al系列 深喉型气动压力机 fbq-al series of long deed throat pneumatic press machine)

根据客户需求可定做非标准压机 (non-standard press can be customized according to customer demand.)

产品特点(product feature)

- 1.以压缩空气为动力源，操作简单。(compressed air as power source , easy to operate.)
- 2.用电脑控制器控制，占用空间小，操作方便，外形美观。(adopt microcomputer control , use small space , easy to operate , beautiful appearance.)
- 3.没有油压系统待机时产生的噪音，可节省电力消耗从而降低生产成本。(no hydraulic system noise , can save electricity consumption and thus reduce production costs.)
- 4.出力调整容易，只要调整汽压压力，就能达到所需压力。(output adjustment as easy as adjusting the air pressure , can achieve the required pressure.)
- 5.安全设计，采用双手操作，设有急停和上下点动功能。(safety design , using both hands to operate , with mergency stop and jog up and down function.)
- 6.多功能用途，适用于压入轴承、冲孔、铆合、装配、切断等。(multi-use , for

pressing , punching , riveting , assembly , cutting and so on.)

7.操作是如需快速下降，可选配快速排气阀。（ higher fast-forward speed requested , quick exhaust valve can be configured (optional))

技术参数 technical parameters

model	型号	单位/unit	fbq-al2000
max working height	最大工作高度	mm	260
cylinder stroke	气缸行程	mm	140
table size	工作台尺寸	mm	300 × 250
using pressure	使用压力	mpa	0.4-0.7
mounting hole	模柄尺寸	mm	22
power	电源	v	ac220
using pressure	使用压力	单位/unit	理论压力theory pressure
0.4	0.4	mpa	12.05kn(1205kgf)
0.5	0.5	mpa	15.07kn(1507kgf)
0.6	0.6	mpa	18.08kn(1808kgf)
0.7	0.7	mpa	21.10kn(2110kgf)
weight	重量	kg	287