

精密单柱液压机 弓形单柱液压机 高精密单柱液压机

产品名称	精密单柱液压机 弓形单柱液压机 高精密单柱液压机
公司名称	玉环方博机械有限公司
价格	.00/台
规格参数	
公司地址	浙江台州玉环汽摩园工业区
联系电话	0576-87216855 13967655592

产品详情

带plc控制面板液压机，数控型单柱液压机，日亿品牌液压机出口销售，我司液压机精密度，作用范围广，我司产品元件为进口元件，性能好，设计安全，自动化单柱液压机供应，玉环高精度单柱液压机销售，精密液压机，立式单柱液压机，有意者请致电：13967655592
0576-87216855，何女士。或者发送邮件至fangbo.cn@163.com或者登陆我司官网www.fangbo.cn.com

fbv-e 系列 高精度数控单柱液压机 (plc控制、人机界面)

fbv-e series of high precision cnc single column hydraulic press (plc control, man-machine interface)

(根据客户需求可定做非标专机)

non-standard press can be customized according to customer demand

产品特点 product feature

1. c型单柱设计，机身整体铸造，经过高温时效处理，刚性好，变形量小。

the c-body design, whole body casting, after high temperature aging treatment,

, rigid and stable, the deformation is small

2. 采用plc控制，在屏幕上任意设定动作速度、压力、时间、下压位置精度高，可靠性能好。

plc control, on the screen can be arbitrary set speed, pressure, time, repeated high positioning accuracy, good performance.

3. 配有液压系统传感器和压力传感器，显示实际压力，可设置压力检测范围，检测压装的产品是否合格，产品在压装过程中超压和欠压都会自动报警并停机。

equipped with sensors in hydraulic system and pressure sensors, display actual pressure, pressure detection range can be set, detection of press-fit products are qualified, products in the process of pressing, overvoltage and undervoltage will automatically alarm and shutdown.

4. 全油压系统，压力大，工作性能稳定，压力精度高、调节范围大。

the whole hydraulic system, the pressure is strong, the work performance is stable, the accuracy of the pressure is high, the adjustment range is large.

5. 安全设计，采用全自动操作和双手操作，设有急停及上下点动功能。

security design, using both hands to operate, with emergency stop and jog up and down function.

6. 主轴下行时具有快进和增压工进两种速度，快进提高工作效率：增压工进速度可任意调节，提高产品压装质量，保护模具和产品。可根据用户要求，另配置进口plc、光栅保护以及人机界面（触摸屏）等先进元器件。对于客户的特殊要求，我们可以特别设计生产，最大限度的满足客户生产工艺要求。

spindle down, with two speeds, fast-forward and slow forward, fast forward speed is fast and can improve work efficiency; slow forward speed can be adjusted, to improve the quality of press-fit, protection of mold and products.

7. 采用手动按钮与脚踏两种循环启动方式。

two of the cycle start-up mode: buttons and pedals

8. 整机控制系统采用进口高端名牌产品，plc，触摸屏采用西门子、三菱、威纶等高端品牌，液压系统采用进口双比例系统阀（具体配置见配置清单）。

the whole control system is using imported high-end brand-name products, plc, the touch screen is the use of high-end brands such as siemens, mitsubishi, wei lun, the hydraulic system is the use of imported dual proportional system valve (specific configuration, see the configuration list)

9. 密封件采用日本nok和台湾鼎基。

the seal is nok from japan and taiwan tripod base, hydraulic fittings using brand-name products of taiwan

10. 红外线操作安全保护感应装置（根据客户需求选配）。

infrared protection device (according to customer's requirements)

技术参数 technical parameters

specifications	规格	单位	fbv-e01
rated oil pressure	额定油压	mpa	4
theoretical output pressure	理论压力	kn	10(1t)
max stroke	最大行程	mm	150
max opening height	最大开口高度	mm	260
throat depth	喉深	mm	140
fast-forward speed	快下速度	mm/s	100
working speed	工进速度	mm/s	5-50
return speed	回程速度	mm/s	120
the height of the working table	工作台距地面高度	mm	850
the size of the working table	有效工作台尺寸(前后*左右)	mm	275x400
mold mounting hole	模柄尺寸	mm	¢ 22
power of motor	油泵电机功率	kw	2.2
power(3 ac,50hz)	电源(3 ac,50hz)	v	380
weight	机床总重量(约)	kg	470