

10吨液压旋铆机生产 专业数控液压旋铆机

产品名称	10吨液压旋铆机生产 专业数控液压旋铆机
公司名称	玉环方博机械有限公司
价格	.00/台
规格参数	
公司地址	浙江台州玉环汽摩园工业区
联系电话	0576-87216855 13967655592

产品详情

生产自动化液压旋铆机，数控型液压旋铆机供应，高精度数控液压铆接机，可根据用户要求，另配置进口plc、光栅保护以及人机界面（触摸屏）等先进元器件。对于客户的特殊要求，我们可以特别设计生产，最大限度的满足客户生产工艺要求。有意者请致电：13967655592
0576-87216855，何女士。或者发送邮件至fangbocn@163.com或者登陆我司官网www.fangbocn.com

fby-xc系列 数控液压旋铆机 (fby-xc series of cnc hydraulic riveting machine)

根据客户需求可定做非标准压机 (non-standard press can be customized according to customer demand.)

产品特点(product feature)

1.c型机身设计，占用空间小，方便操作。 (the-c-body design , use small space and easy to operate.)

2.专业设计，适用于各种零部件的翻遍铆合作业，如球头、硅油离合器等。 (professional design , suitable for various parts of the flange riveting , such as ball , silicone oil clutch.ect.)

3.变频动力头，转速任意调节，作用范围广。 (frequency power head , adjusting speed arbitrary , wide speed range.)

4.安全设计，采用双手操作，设有急停和上下点动功能。 (safety design , using both hands to operate , with emergency stop and jog up and down function.)

5.按键与脚踏两种循环启动方式，任意调整下压速度与时间。 (key and foot switch two cycle start modes , pressure speed and time can be adjusted arbitrarily)

6.可选配扭力检测装置，方便检测球头零件的旋铆质量（球头专机）。 (can be equipped with a torque detection device to facilitate the detection of spin riveting quality(ball special purpose machine.)

7.可根据用户要求配置红外线保护装置。 (infrared protection can be configured(optional))

specifications	规格	单位 unit	fby-xc10
theoretical output pressure	理论出力	kn	100(10t)
rated oil pressure	额定油压	mpa	12
max stroke	最大行程	mm	120
max opening height	最大开口宽度	mm	200
throat depth	喉深	mm	200
fast-forward speed	快进速度	mm/s	100
feeding speed	工进速度	mm/s	10~70
return speed	回程速度	mm/s	230
the size of the working table	工作台尺寸	mm	650 x400
spin riveting motor power	旋铆电机功率	kw	4
spindle motor speed	主轴转速范围	rpm	10~1400(变频调速)
power of motor	油泵电机功率	kw	4
power(3 ac,50hz)	电源(3 ac,50hz)	v	380
weight	重量	kg	1250

