

## D 667钴基焊条

产品名称	D 667钴基焊条
公司名称	南宫市宇联耐磨焊条厂
价格	280.00/公斤
规格参数	
公司地址	中国 河北邢台市 河北省南宫市李家村
联系电话	15233945500 13930916962

## 产品详情

category 类别	trade- 牌号	markequivalent to china standard 相当国标	characteristics & application 特性和用途
hard-surfacing 硬 面 堆 焊	d 667	edzcr-b-15	hrc 48. resistance to wear, gas corrosion and oxidation. hardfacing of blast furnace hopper and cracker part. hrc 48, 耐磨、耐气蚀、抗氧化。堆焊高炉料钟、破碎料斗。
	d 802	edcocr-a-03	hrc38-47. resistance to heat, wear and corrosion. hardfacing of high temperature part such as the edge of thermo-cutter. hrc38-47, 耐热、耐蚀、耐磨。堆焊高温工件如热剪切刀。
	d 812	edcocr-b-03	hrc45-50. resistance to heat, wear and corrosion. hardfacing of high temperature part such as internal-combustion engine valve. hrc45-50, 耐热、耐蚀、耐磨。堆焊高温工件如内燃机阀。
	d 822		hrc 53. resistance to wear and heat, bad shock resistance. hardfacing of rotating blade wheel of boiler. hrc 53, 耐热、耐磨, 但抗冲击性差。堆焊锅炉旋转叶轮。
	d 832	edcocr-c-03	hrc 50. wear and heat resistance. hardfacing of high temperature part.

such as hot-rolling guided way.

hrc 50 , 耐热、耐磨。堆焊高温工件如热轧导轨

d 842 edcocr-d-03

hrc28-38. corrosion and thermo-fatigue resistance, work hardening  
hardfacing of hot forging die.

hrc28-38 , 耐蚀、抗热疲劳 , 具有加工硬化性。堆焊热锻

category	trade mark	chemical composition	characteristics & application
类别	牌号	主要成份(%)	特性和用途
hardfacing 硬 面 堆 焊	s 101	c3 cr28 ni4 si3.5 fe rem.	hrc48-54. resistance to wear, gas corrosion and oxidation. hardfacing of bucket tooth and case pump. hrc48-54 , 耐磨、耐气蚀、抗氧化。堆焊铲斗齿 , 泵套
	s 111	c1 cr29 w5 co rem.	hrc38-47. resistance to wear and corrosion at high-temperature. hardfacing of high temperature and pressure valve. hrc38-47 , 高温下耐磨、耐蚀。堆焊高温高压阀门
	s 112	c1.5 cr29 w8 co rem.	hrc45-50. resistance to wear and corrosion at high-temperature. hardfacing of valve and hot-rolling pass. hrc45-50 , 高温下耐磨、耐蚀。堆焊阀门 , 热轧孔型
	s 113	c2.5 cr30 w17 co rem.	hrc 55. wear and heat resistance at high temperature, bad shock resistance. hardfacing of screw charging carriage. hrc 55 , 高温下耐磨、耐热 , 但抗冲击性差。堆焊螺旋送料机用
	s 114	c2.5 cr30 w12 co rem.	hrc 53. wear and heat resistance at high temperature, bad shock resistance. hardfacing of three-cone bit. hrc 53 , 高温下耐磨、耐热 , 但抗冲击较差。堆焊牙轮钻头