

# 优质美标不锈钢球阀

产品名称	优质美标不锈钢球阀
公司名称	江苏诚一阀门有限公司
价格	面议
规格参数	
公司地址	江苏省连云港市灌南县经济开发区
联系电话	86-051883887898 13851230690

## 产品详情

q41不锈钢美标球阀主要外形及连接尺寸表

公称压力	公称通径	d	l	d	d1	d2	b	f	z- d	h	w
class 150	1/2"	13	108	89	60.5	35	11.5	1.6	4-16	79	135
	3/4"	19	117	98	70	43	11.5	1.6	4-16	84	135
	1"	25	127	108	79.5	51	12	1.6	4-16	95	170
	1-1/4"	32	140	117	89	64	13	1.6	4-16	103	170
	1-1/2"	38	165	127	98.5	73	15	1.6	4-16	111	200
	2"	51	178	152	120.5	92	16	1.6	4-19	120	200
	2-1/2"	64	190	178	139.5	105	18	1.6	4-19	153	300
	3"	76	203	190	152.5	127	19	1.6	4-19	163	300
	4"	102	229	229	190.5	157	24	1.6	8-19	182	400
	5"	127	356	254	216	186	24	1.6	8-22	260	500
class 300	6"	152	394	279	241.5	216	26	1.6	8-22	280	800
	8"	203	457	343	298.5	270	29	1.6	8-22	-	1100
	1/2"	13	140	95	66.5	35	15	1.6	4-16	79	135
	3/4"	19	152	117	82.5	43	16	1.6	4-19	84	135
	1"	25	165	124	89	51	18	1.6	4-19	95	170
	1-1/4"	32	178	133	98.5	64	19	1.6	4-19	103	170
	1-1/2"	38	190	156	114.5	73	21	1.6	4-22	111	200
	2"	51	216	165	127	92	23	1.6	4-22	120	200
2-1/2"	64	241	190	149	105	26	1.6	8-19	153	300	

	3"	76	283	210	168.5	127	29	1.6	8-22	163	300
	4"	102	305	254	200	157	32	1.6	8-22	182	400
	5"	127	381	279	235	186	35	1.6	8-22	260	500
	6"	152	403	318	270	216	37	1.6	12-22	280	800
	8"	203	502	381	330	270	42	1.6	12-25	-	1100

q41f-10k-20k 日标球阀

公称 压力	公称 口径	d	l	d	d1	d2	b	f	z- d	h	w
jis10k	15	15	108	95	70	52	12	1	4-15	79	135
	20	20	117	100	75	58	14	1	4-15	84	135
	25	25	127	125	90	70	14	1	4-19	95	170
	32	32	140	135	100	80	16	2	4-19	103	170
	40	38	165	140	105	85	16	2	4-19	111	200
	50	50	178	155	120	100	16	2	4-19	120	200
	65	64	190	175	140	120	18	2	4-19	153	300
	80	76	203	185	150	130	18	2	8-19	163	300
	100	100	229	210	175	155	18	2	8-19	182	400
	125	125	356	250	210	185	20	2	8-23	260	500
	150	150	394	280	240	215	22	2	8-23	280	800
200	200	457	330	290	265	22	2	12-23	-	1100	
jis20k	15	15	140	95	70	52	14	1	4-15	79	135
	20	20	152	100	75	58	16	1	4-15	84	135
	25	25	165	125	90	70	16	1	4-19	95	170
	32	32	178	135	100	80	18	2	4-19	103	170
	40	38	190	140	105	85	18	2	4-19	111	200
	50	50	216	155	120	100	18	2	8-19	120	200
	65	64	241	175	140	120	20	2	8-19	153	300
	80	76	283	200	160	135	22	2	8-23	163	300
	100	100	305	225	185	160	24	2	8-23	182	400
	125	125	381	270	225	195	26	2	8-25	260	500
	150	150	403	305	260	230	28	2	12-25	280	800
200	200	502	350	305	275	30	2	12-25	-	1100	

产品特点 适用介质：水、气、油品、天然气和酸碱腐蚀性介质。适用温度：-20 ~ 450  
 驱动方式：手动、气动、电动、液动等。公称通径：dn 15-500 1/2" ~ 20"

q41不锈钢美标球阀主要零件材料

名称		wcb类	cf8类	cf3类	cf8m类	cf3m类
阀体左体		a216-wcb	a315-cf8	a35-cf3	a351-cf8m	a351-cf3m
球体	b2-b8	a105-1025	a182-f304l	a182-f304l	a132-f316	a182-f316l
	b8以上	a216-wcb	a351-cf8m	a351-cf3	a351-cf8m	a351-cf3m
阀杆		a182-f6a	a182-f304	a182-f304l	a182-f336	a182-f316l
阀座		ptfe/增强ptfe/nylin ptfe/reinforced ptfe/nyion				
阀座支承圈		a105-1025	a182-f304	a182-f304l	a182-f316	a182-f316l
弹簧			3yc-7/17-49h			
o形圈		nbr	氟橡胶			
螺柱		a193-b7	a193-b8			
螺母		a194-2h	a194-8			

以上信息由江苏诚一阀门有限公司提供，更多详情等登陆我公司网站<http://www.cncyv.com>  
 /或进入本产品详细页<http://www.cncyv.com/74.html>