

D7T1X型 对夹式蝶阀

产品名称	D7T1X型 对夹式蝶阀
公司名称	天津高能阀门有限公司
价格	100.00/台
规格参数	
公司地址	天津滨海新区丹江路1068号
联系电话	022-66291299 13174883888

产品详情

产品特点produce features:

- 1、小巧轻便，易于拆装及维修，可在任意位置安装。
- 2、结构简单、紧凑，90 ° 回转启闭迅速。
- 3、阀板可双向承压，达到完全密封，气体试验泄漏为零。
- 4、流量特性趋于直线，调节性能好。
- 5、多种材质配置，适用不同介质。
- 6、抗冲刷性能好，适用于较恶劣工况环境。
- 7、中心板式结构，启闭力矩小。
- 8、启闭试验多达数万次，使用寿命长。
- 9、可用于介质截断和调节。

1. it is small in size & light in weight and easy installation and maintenance. it can be mounted wherever needed.
2. simple and compact structure, quick 90 ° degree on-off operation.
3. disc has two-way bearing, perfect seal, without leakage under the pressure test.
4. flow curve tending to straight-line. excellent regulated performance.

5. various kinds of materials applicable to different medium.
6. strong wash and brush resistance, and can fit to bad working condition.
7. center plate structure, small torque of open and close.
8. long service life. standing the test of ten thousands opening and closing operation.
9. can be used in cutting off and regulation medium.

产品执行标准：product standard:

设计标准 design standard	结构长度 face to face dimensions	侧法兰标准 flange standard	试验检验标准 test and check up standard
gb/t 12238、 api 609	api 609	gb/t 17241.6、 ansi b16.1	gb/t 13927、 api 598

主要性能参数main performance parameters:

公称压力 nominal pressure pn/(mpa)	公称通径 nominal diameter dn(mm)	试验压力 testing pressure (mpa)		适用温度 suitable temp ° c	适用介质 suitable media	
		壳体shell	密封 seal			
1.0	50 ~ 350	1.5	1.1	- 15 ~ +150	淡水、污水、海水、空气、 蒸汽、食品、药品、各种油类、 酸类、碱类等 fresh water, sewage, sea water, air, vapor, food, medicine, oils, acids,	手柄 电动

1.6		2.4		1.76					alkalis, etc.			electr
-----	--	-----	--	------	--	--	--	--	---------------	--	--	--------

主要连接尺寸及重量 outline dimensions & connection dimensions & weight:

规格 size dn(mm)	a	b	c	d1	l	n- \varnothing	k	e	4- \varnothing 1	\varnothing 2	g	重量 weight kg
50	140	80	43	125	32	4-19	77	57.15	4-6.7	12.6	100	3.34
65	152	89	46	145	32	4-19	77	57.15	4-6.7	12.6	120	3.94
80	159	95	45.21	160	32	8-19	77	57.15	4-6.7	12.6	127	4.05
100	178	114	52.07	180	32	8-19	92	69.85	4-10.3	15.77	156	5.48
125	190	127	55.5	210	32	8-19	92	69.85	4-10.3	18.92	190	7.66
150	203	139	55.75	240	32	8-23	92	69.85	4-10.3	18.92	212	8.5
200	238	175	60.58	295	45	8-23	115	88.9	4-14.3	22.1	268	25
250	268	203	68	350	45	12-23	115	88.9	4-14.3	28.45	325	31.4
300	306	242	76.9	400	45	12-23	140	107.95	4-14.3	31.6	403	45.9
350	368	267	76.17	460	45	16-23	140	107.95	4-14.3	31.6	436	54

注：表中的连接尺寸以pn1.0mpa为例，实际产品中dn50~dn350规格的d1和n- \varnothing 尺寸包容了pn1.0mpa、pn1.6mpa和ansi cl 125三种法兰连接标准。

note: the dimensions d1 and n- \varnothing are listed in above table show the installation dimensions of butterfly valve. it contains china standard (gb), international standard (iso), germany standard (din), and england standard (bs) of flange connection standard, etc.