

不锈钢、碳钢、灰铸铁

碳钢、不锈钢

不锈钢

橡胶、四氟、不锈钢、硬质

耐1100度高温手动插板阀主要外形及连接尺寸(mm)

MPa	DN	L	D	D1	D2	H	N-M	D0
1.0	50	43	160	125	100	285	4-M16	180
	65	46	180	145	120	298	4-M16	180
	80	46	195	160	135	315	4-M16	220
	100	52	215	180	155	365	8-M16	220
	125	56	245	210	185	400	8-M16	230
	150	56	280	240	210	475	8-M20	280
	200	60	335	295	265	540	8-M20	360
	250	68	390	350	320	630	12-M20	360
	300	78	440	400	368	780	12-M20	400
	350	78	500	460	428	885	16-M20	400
	400	102	565	515	482	990	16-M22	400
	450	114	615	565	532	1100	20-M22	530
	500	127	670	620	585	1200	20-M22	530
	600	154	780	725	685	1450	20-M27	600
	700	165	895	840	800	1700	24-M27	600
	800	190	1010	950	898	2000	24-M30	680
900	203	1110	1050	1005	2300	28-M30	680	
1000	216	1220	1160	1115	2500	28-M30	700	
1200	254	1450	1380	1325	2800	32-M36	800	
1.6	50	43	160	125	99	285	4-M16	180
	65	46	185	145	120	295	4-M16	180
	80	46	200	160	135	315	8-M16	220
	100	52	220	180	155	365	8-M16	220
	125	56	250	210	185	400	8-M16	230
	150	56	285	240	210	475	8-M20	280
	200	60	340	295	265	540	12-M20	360
	250	68	405	355	310	630	12-M22	360
	300	78	460	410	375	780	12-M22	400
	350	78	520	470	435	885	16-M22	400
	400	102	580	525	485	990	16-M27	400
	450	114	640	585	545	1100	20-M27	530
500	127	715	650	609	1200	20-M30	530	