陶瓷方解石粉（方角石粉）325-11000目

产品名称	陶瓷方解石粉（方角石粉）325-11000目
公司名称	广州亿峰化工科技有限公司
价格	1.00/千克
规格参数	产地:台资 caco3＞:98（%） fe2o3＜:0.03（%）
公司地址	广州高新技术产业开发区科学大道122-124号（B2栋）1818房
联系电话	13503090280 13728083267

产品详情

厂商	台资	caco3＞	98（%）
fe2o3＜	0.03（%）	whiteness>	-
粒度	325-7000目		

超细方解石粉

	200目	400目	600目	800目	1250目	2000目	3000目
碳酸钙	≥98%	≥98%	≥98.8%	≥98.8%	≥99%	≥99%	≥99%
三氧化二铁	≤0.03%	≤0.03%	≤0.03%	≤0.03%	≤0.03%	≤0.03%	≤0.03%
二氧化硅	≤0.05%	≤0.05%	≤0.05%	≤0.05%	≤0.05%	≤0.05%	≤0.05%
三氧化二铝	≤0.15%	≤0.15%	≤0.15%	≤0.15%	≤0.15%	≤0.15%	≤0.15%
ph值	8-9	8-9	8-9	8-9	8-9	8-9	8-9
水份	≤0.3%	≤0.3%	≤0.3%	≤0.3%	≤0.3%	≤0.3%	≤0.3%
白度	≥93	≥94	≥94	≥95	≥95	≥95	≥95
吸油量g/100g	10-15	13-16	15-18	17-20	20-23	23-26	31-34
吸水量g/100g	0.35	0.4	0.43	0.45	0.48	0.52	0.59

超细方解石粉：经天然方解石研磨粉碎气流分级精制而成。其产品粒径小、杂质少、白度高、吸油量低、绝缘流动性好等特点。广泛用于塑料、橡胶、涂料、建材、纺织、玻璃、造纸、复合材料等领域.

the english version

vendor

taiwanese

caco3 >

98 (%)

fe2o3 <

0.03 (%)

whiteness >

-

particle size

325-7000 mesh

ultrafine calcite powder

200 mesh

400 mesh

600 mesh

800 mesh

1250 mesh

2000 mesh

3000 mesh

calcium carbonate

98% or higher

98% or higher

98.8% or higher

98.8% or higher

99% or higher

99% or higher

99% or higher

ferric oxide

0.03% or less

0.03% or less

0.03% or less

0.03% or less

0.03% or less

0.03% or less

0.03% or less

silica

0.05% or less

0.05% or less

0.05% or less

0.05% or less

0.05% or less

0.05% or less

0.05% or less

3 oxidation 2 aluminium

0.15% or less

0.15% or less

0.15% or less

0.15% or less

0.15% or less

0.15% or less

0.15% or less

the ph

eight to nine

eight to nine

eight to nine

eight to nine

eight to nine

eight to nine

eight to nine

the moisture

0.3% or less

0.3% or less

0.3% or less

0.3% or less

0.3% or less

0.3% or less

0.3% or less

white degree

93 or more

94 or more

94 or more

95 or more

95 or more

95 or more

95 or more

oil absorption g / 100 g

10-15

13-16

15-18

17-20

20-23

23-26

31-34

water quantity g / 100 g

0.35

0.4

0.43

0.45

0.48

0.52

0.59

calcite powder, ultrafine jingtianran calcite grinding crushing flow classification. the product particle size small, little impurity, high whiteness, good liquidity, low oil absorption, insulation, etc. widely used in plastics, rubber, coatings, building materials, textiles, glass, paper, composite materials and other fields.

"供应陶瓷方解石粉（方角石粉）325-11000目"的颜色为白色，Fe2O3＜是0.03（%），CaCO3＞为98（%），粒度是325-11000（目），白度>为92（%），产地是台资