

光电接触两用转速表 多功能转速表DT6236B 数字式转速测量仪

产品名称	光电接触两用转速表 多功能转速表DT6236B 数字式转速测量仪
公司名称	深圳市欣宝瑞仪器有限公司
价格	320.00/台
规格参数	加工定制:是 品牌:sampo/欣宝 型号:dt6236b
公司地址	深圳市宝安区新安街道41区8号楼(华丰新安青年创业基地)九楼905、908、910号
联系电话	0755-27863686 13760299409

产品详情

光电接触两用转速/线速表dt6236b

5位大屏幕液晶黄色背光显示器,字高18mm

测试范围:

光电转速方式:2.5~99,999rpm

接触转速方式:0.5~19,999rpm

接触线速方式:0.05~1,999.9m/min

分辨率:

光电转速:0.1rpm(2.5~999.9rpm)

1rpm(1,000rpm以上)

接触转速:0.1rpm(0.5~999.9rpm)

1rpm(1,000rpm以上)

接触线速:0.01m/min(0.05~99.99m/min)

0.1m/min(100m/min以上)

准确度：± (0.05%+1个字)

采样时间：0.5秒(120rpm以上)

量程选择：自动切换

有效距离：50~500mm

工作电流：最大55ma

记忆：自动记忆最大值，最小值，最后测量值

自动存储最多96个数据

电源：4x1.5v aa电池

photo/contact tachometer

surface speed meter

model: dt6236b

5 digits 18mm (0.6") yellow backlight lcd

accuracy: ± (0.05%+1 digit)

sampling time: 0.5 sec(over 120rpm)

range select: auto-ranging

memory: max. value, min. value,

last value. can store 96s data.

time base: 6mhz quartz crystal

detecting distance: 50~500mm

measuring range:

photo tach: 2.5~99,999rpm

contact tach: 0.5~19,999rpm

surface speed: 0.05~1,999.9m/min

resolution:

photo tach: 0.1rpm(2.5~999.9rpm)

1rpm(over 1,000rpm)

contact tach: 0.1rpm(0.5~999.9rpm)

1rpm(over 1,000rpm)

surface speed: 0.01m/min(0.05~99.99m/min)

0.1m/min(over 100m/min)

battery: 4x1.5v aa battery

"供应光电接触两用转速表 多功能转速表DT6236B 数字式转速测量仪"的重量为0.18 (kg) ，类型是数字式转速计，型号为DT6236B，测量精度是0.05%+1个字，尺寸为210*74*37 (mm) ，品牌是SAMPO/欣宝，测量电流范围为10 (A) ，加工定制是是，测量电压范围为12 (V)