超胜焊机 等离子切割机CUT-40A LGK40A等离子切割 逆变焊机

产品名称	超胜焊机 等离子切割机CUT-40A LGK40A等离子切割 逆变焊机		
公司名称	河北瓦尔丁科技有限公司		
价格	1250.00/台		
规格参数	类型:空气等离子切割机 品牌:超胜 电流:交流		
公司地址	河北省廊坊市安次区杨税务镇联东U谷- 廊坊国际企业港(A区)11#D-1单元501厂房		
联系电话	13292608899		

产品详情

cut-40a lgk40a等离子切割 逆变焊机

名称:超胜焊机等离子切割机

品牌:广州超胜

型号: cut-40a lgk40a

厂家配置:切割枪40a1把、地线一套、说明书合格证各一份。

邮费说明:运费请查看运费说明,不同的地方运费不一样的。自行拍下的客人请自行按照运费说明填外,如果是发物流,请咨询卖家。。。。

功能特点:

空气等离子切割机是以高温高压的等离子弧为热源,当电弧的弧柱和高速气流通过割矩喷嘴小孔时,使电弧的热能集中(压缩)程度提高,将被切割金属局部熔化,并同时用高速气流将熔化的金属吹走,而形成狭窄切口采用目前最先进的逆变技术,性能优良体积小,重量轻,特别是移动作业时,更是方便效率高,节省电能切割电流连续可调,易于实现相应板厚的精美切割动态性能好,电弧集中,割缝窄,切口平滑可切割碳钢,不锈钢,铜,铝等各种有色金属。

号	cut-40	cut-60	cut-80	cut-100	
输入电压(v)	单相380	单相380	单相380	单相380	
频率(hz)	50	50	50	50	
输入功率(kva)	4	7	10	14	

空载电压(v)	196	250	255	255
工作电压(v)	80-100	90-110	100-120	110-130
工作电流(a)	20-40	20-60	20-80	30-100
负载持续率(%)	60	60	60	60
最大切割厚度	12	16	20	25
工作气压(kg/cm2	2.0-3.5	2.5-4.0	4.0-4.5	4.0-4.5
)				
重量(kg)	11	16	24	25

cut—inverter air plasma cutter cutting current can adjust at will,easy to realize,excellent cutting quality of various thickness metal. energy saved,light weight easy to operation because of using inverter technology,then the cutter have the virtue of fine dynamic character,arc concentration,narrow cutting seam,smooth incision. it is more safe and reliable for using compressed air instead of expensive gas. narrow in seam,glazed in face of cut,no distortion of workpiece and high utilization ratio of plate. used for cutting stainless steel,carbon-steel,copper and aluminum,etc. various shapes of cutting can be realized in multi-station.

"超胜焊机 等离子切割机CUT-40A LGK40A等离子切割 逆变焊机"的频段为中频,作用原理是逆变,最大切割厚度为10(mm),驱动形式是电动,作用对象为金属,类型是空气等离子切割机,产品别名为等离子切割机,型号是CUT-40A,电流为交流,品牌是超胜,用途为切割,控制方式是手动,等离子源为空气,动力形式是等离子