

# 金桥棉纺专用型络筒机 络筒机

产品名称	金桥棉纺专用型络筒机 络筒机
公司名称	张家港市金桥轻工机械有限公司
价格	340000.00/台
规格参数	加工定制:是 种类:络筒机 品牌:jq
公司地址	张家港市塘桥镇青龙村上相
联系电话	58435120 13962292688

## 产品详情

张家港金桥轻工机械

欢迎来电 徐滔 13962292688

棉纺包芯纱（专用）络筒机

jq15325 cone winding machine

该络筒机是专为大圆织机厂以及棉纺织厂、毛纺织厂，在细纱机上加工，氨纶品种除外各种包芯纱丝而特别设计制造的，解决了生产包芯纱过程中纱线张力问题，每锭三只管筒同时卷绕，使其生产效率、产量、成型、松紧度和最终产品质量达到所有客户要求。

this cone winding machine is designed for great circle loom factory and textile factory,wool en mill.it is specially designed for various kinds of core-spun yarn except spandex to processed on the spinning frame.it solved the thread tension problem during the producing of core-spun yarn.three winding drums per spindle to wind up improve production efficiency, output,shaping,tension and quality of final products to meet all customer needs.

技术参数（technical parameter）：

名称	machine type	jq1 5325
控制方式	conrol mode	衡线速控制 value-wire-speed control
生产速度	production speed	600米/分 600 m/min
起动速度	start-up speed	1-300秒可调 1-300 seconds is adjustable
定长设置	fixed-length settings	100-990000米可调 100-990000 meters is adjustable

驱动方式	driven mode	每锭、二台交流电机、一台专用变频器 every spindle,two sets of ac motor,one special inverter
张力调整	tension adjustment	每锭配：可调式张力器 allocation of each spindle:adjustable tension device
卷绕筒管	winding bobbin	85mm * 58mm
卷绕直径	winding diameter	250mm * 45mm
每节锭数	the number of each ingot	5锭 ( 每锭三只筒管 5 spindles ( 3 bobbins/spindle )
供电电压	supply voltage	三相220v 50-60hz three-phase 220v 50-60hz
安装尺寸	installed-size	1990*700*1400 mm (l*w*h mm)
适应品种	adapt varieties	锦纶、涤纶、涤丙复合丝 ( 粘胶丝 ) , pbt、poy、fdy等 nylon,polyester,polyester/propylene compound fiber(viscose filament),pbt,poy,fdy,etc.

"供应金桥棉纺专用型络筒机"的品牌为JQ，种类是络筒机，加工定制为是