

带扳手弹簧微启式安全阀 上海远大阀门

产品名称	带扳手弹簧微启式安全阀 上海远大阀门
公司名称	上海远大阀门有限公司
价格	688.00/个
规格参数	加工定制:是 品牌:上海远大阀门 型号:a47h-16c
公司地址	上海市青浦区外青松公路3885号
联系电话	86-02139822878 18049757692

产品详情

本阀门适用于工作温度 350 的蒸汽、空气等介质的设备或管路上。作为超压保护装置。连接法兰标准按jb/t-94的系列1。

主要零部件材料

外形尺寸和连接尺寸

型号	公称 口径	do	d	k	g	g1	b	f	f1	z- ø d	dn	d1	k1	g2	g'	b 1	f'	f1'	z1-ø d 1	l	l1	h
a47h-16 c	20	15	10	75		55	1	2		4-14	20	10	75	55		1	2		4-14	10	85	270
			5				6					5				6				0		
	25	20	11	85		65	1	2		4-14	25	11	85	65		1	2		4-14	10	85	270
			5				6					5				6				0		
	32	25	14	10		78	1	2		4-18	32	14	10	78		1	2		4-18	11	10	312
			0	0			8					0	0			8				5	0	
	40	32	15	11		85	1	3		4-18	40	15	11	85		1	3		4-18	12	11	320
			0	0			8					0	0			8				0	0	

50 40 16 12 10 2 3 4-18 50 16 12 10 2 3 4-18 13 12 390
5 5 0 0 5 5 0 0 5 0

65 50 18 14 12 2 3 4-18 65 18 14 12 2 3 4-18 14 13 395
5 5 0 0 0 0 5 5 0 0 0 0

80 65 20 16 13 2 3 8-18 80 20 16 13 2 3 8-18 16 13 400
0 0 5 0 0 0 0 0 5 0 0 5

10 80 22 18 15 2 3 8-18 10 22 18 15 2 3 8-18 17 16 600
0 0 0 0 5 2 0 0 0 5 2 0 0 0

12 10 25 21 18 2 3 8-18 12 25 21 18 2 3 8-18 19 19 620
5 0 0 0 5 2 5 0 0 5 2 0 0

15 12 28 24 21 2 3 8-23 15 28 24 21 2 3 8-23 20 19 625
0 5 5 0 0 4 0 5 0 0 4 5 5

20 15 34 29 26 2 3 12-2 20 34 29 26 2 3 12-23 24 23 798
0 0 0 5 5 6 3 0 0 5 5 6 0 0

25 20 40 35 32 3 3 12-2 25 40 35 32 3 3 12-26 35 32 981
0 0 5 5 0 0 6 0 5 5 0 0 0 0

30 25 46 41 37 3 4 12-2 30 46 41 37 3 4 12-26 35 32 1005
0 0 0 0 5 0 6 0 0 0 5 0 0 0

a47h-25 20 15 10 75 55 1 2 4-14 20 10 75 55 1 2 4-14 10 85 270
5 6 5 6 0 0

25 20 11 85 65 1 2 4-14 25 11 85 65 1 2 4-14 10 85 270
5 6 5 6 0 0

32 25 14 10 78 1 2 4-18 32 14 10 78 1 2 4-18 11 10 312
0 0 8 0 0 8 5 0

40 32 15 11 85 1 3 4-18 40 15 11 85 1 3 4-18 12 11 320
0 0 8 0 0 8 0 0

50 40 16 12 10 2 3 4-18 50 16 12 10 2 3 4-18 13 12 390
5 5 0 0 5 5 0 0 5 0 0 0 5 0

65 50 18 14 12 2 3 8-18 65 18 14 12 2 3 4-18 14 13 395
5 5 0 2 5 5 0 0 5 0 0 0 0 0

80 65 20 16 13 2 3 8-18 80 20 16 13 2 3 8-18 16 13 400
0 0 5 4 0 0 5 0 0 5 0 0 0 5

10 80 23 19 16 2 3 8-23 10 22 18 15 2 3 8-18 17 16 600
0 0 0 0 0 4 0 0 0 0 5 0 0 0

12 10 27 22 18 2 3 8-26 12 25 21 18 2 3 8-18 19 19 620
5 0 0 0 8 8 5 0 0 5 2 0 0 0

15 12 30 25 21 3 3 8-26 15 28 24 21 2 3 8-23 20 19 625
0 5 0 0 8 0 0 5 0 0 4 5 5

20 15 36 31 27 3 3 12-2 20 34 29 26 2 3 12-23 24 23 798
0 0 0 0 8 4 6 0 0 5 5 6 0 0

25 20 42 37 33 3 3 12-3 25 40 35 32 3 3 12-26 35 32 981
0 0 5 0 2 6 0 0 5 5 0 0 0 0

30 25 48 43 39 4 4 16-3 30 46 41 37 3 4 12-26 35 32 1005
0 0 5 0 0 0 0 0 0 0 5 0 0 0

a47h-40 20 15 10 75 51 55 1 2 4 4-14 20 10 75 55 1 2 4-14 10 85 270
5 6 5 6 0

25 20 11 85 58 65 1 2 4 4-14 25 11 85 65 1 2 4-14 10 85 270
5 6 5 6 0

32 25 14 10 66 78 1 2 4 4-18 32 14 10 78 1 2 4-18 11 10 312
0 0 8 0 0 8 5 0

40 32 15 11 76 85 1 3 4 4-18 40 15 11 85 1 3 4-18 12 11 320
0 0 8 0 0 8 0 0

50 40 16 12 88 10 2 3 4 4-18 50 16 12 10 2 3 4-18 13 12 390
5 5 0 0 5 5 0 0 5 0

65 50 18 14 11 12 2 3 4 8-18 65 18 14 12 2 3 4-18 14 13 395
5 5 0 0 2 5 5 0 0 0

80	65	20	16	12	13	2	3	4	8-18	80	20	16	13	2	3	8-18	16	13	400
		0	0	1	5	2					0	0	5	0			0	5	
10	80	23	19	15	16	2	3	4.	8-23	10	22	18	15	2	3	8-18	17	16	600
0		5	0	0	0	4		5		0	0	0	5	2			0	0	
12	10	27	22	17	18	2	3	4.	8-26	12	25	21	18	2	3	8-18	19	19	620
5	0	0	0	6	8	8		5		5	0	0	5	2			0	0	
15	12	30	25	20	21	3	3	4.	8-26	15	28	24	21	2	3	8-23	20	19	625
0	5	0	0	4	8	0		5		0	5	0	0	4			5	5	
20	15	37	32	26	28	3	3	4.	12-3	20	34	29	26	2	3	12-23	24	23	798
0	0	5	0	0	2	8		5	0	0	0	5	5	6			0	0	
25	20	45	38	31	34	4	3	4.	12-3	25	40	35	32	3	3	12-26	35	32	981
0	0	0	5	3	5	2		5	4	0	5	5	0	0			0	0	
30	25	51	45	36	40	4	4	4.	16-3	30	46	41	37	3	4	12-26	35	32	1005
0	0	5	0	4	8	6		5	4	0	0	0	5	0			0	0	

"带扳手弹簧微启式安全阀"的结构形式为弹簧式，类型(通道位置)是二通式，标准为国标，公称通径是DN20-DN250 (mm)，加工定制为是，材质是铸钢，流动方向为单向，阀瓣开启高度是微启式安全阀，阀体构造为不封闭式，型号是A47H-16C，规格为DN50，连接形式是法兰，品牌为上海远大阀门，适用介质是蒸汽