

机械密封配件橡胶圈机械密封

产品名称	机械密封配件橡胶圈机械密封
公司名称	嘉善新诚密封件厂
价格	10.00/件
规格参数	加工定制:是 类型:密封圈 材质:橡胶
公司地址	嘉善县罗星街道罗星精密机械创业园5幢208室
联系电话	86-57384838380 13666783111

产品详情

机械密封厂家供应水泵机械密封

厂家供应机械密封 橡胶密封圈

型号：o

适用范围：门窗,汽车,装饰,喷涂,机械,电器,轴承,泵,气缸,托辊,水管,化工管道,阀门

材质：丁腈胶

分类：o型圈

用途：轴用密封,孔用密封,防尘密封,导向环,固定密封,回转密封,油封,水封

形状：o型密封圈

是否标准件：非标准件

性质：耐腐蚀,耐高温,耐磨损

specifications

15 years seal manufacturing experience; oem, odm; products can be replaced of burgman, john crane, flowserve.

nbr	resistant to oil,pressure and wear,good elasticity and mechanical strength;applicable to the mediums including water,oil,alcohol,etc from-20 ° c to 100 ° c .
epdm	resistant to high or low temperatures,ozone and chemicals;applicable to weak acids with temperatures from-30 ° c to 150 ° c
viton	resistant to heat,oil,medicine and chemical reagents,acid and alkali with medium corrosive degrees;applicable to the corrosive medium from -20 ° c to 180 ° c
silica gel	resistant to ozone,aging,acetic acid,ammonia and alcohol,alkali,etc from-50 ° c to 210 ° c
chlorinated rubber	resistant to freon,petroleum;applicable to inorganic acid,alkali,running from-30 ° c to 130 ° c

常规包装：

"机械密封配件橡胶圈机械密封"的是否进口为否，加工定制是是，材质为橡胶，类型是密封圈，型号为橡胶密封，是否标准件是标准件，适用范围为汽车,轴承,泵,釜,油缸,其他，介质是用于油,水有机溶剂以及其它弱腐蚀性溶液等，品牌为机械密封件，样品或现货是现货，性质为耐腐蚀,耐高温,耐高压,耐磨损，使用压力是 1MPa (MPa)，使用温度为-30 ~200 ()