

# ODYSSEY蓄電池PC925 12V28AH工業儲能電池

產品名稱	ODYSSEY蓄電池PC925 12V28AH工業儲能電池
公司名稱	銀杉電源設備（北京）有限公司
價格	1360.00/只
規格參數	類型:儲能用蓄電池 尺寸:見說明 重量:30
公司地址	北京市門頭溝區中門寺街69號43幢2855號（集群註冊）
聯繫電話	13240167776 13240167776

## 產品詳情

### ODYSSEY蓄電池PC925 12V28AH工業儲能電池

#### 優點

- 1、電池活性物質配方，電池容量高於DIN40742標準；
- 2、单体大容量3170AH，避免了電池并聯造成的容量損耗和不平衡；
- 3、氣體復合率大於98%，電池無須加水，低維護量；
- 4、自放電率極低，儲存2年時間無須補充充電；
- 5、循環壽命大於1200次80%DOD；
- 6、能快速回充，大充電電流為40%C10；
- 7、正常使用时沒有酸霧逸出，電池可以安裝在辦公室或設備室；

What is Drycell?

Pure virgin lead; not corrosive in sulfuric acid.

Grids can be made extremely thin.

Thin grids allow more plates per cell.

More plates = more plate surface area.

More surface area for chemical reaction.

Result - 40% greater pulse discharge power, especially for first 5 seconds.

Worlds only pulse power and true deep cycle - all in one battery.

40% more 5 second cranking amps.

400 cycles to % depth of discharge.

High pressure sealed design, explosion-proof and completely safe for in passenger compartment mounting.

Batteries are certified by USDOT and IATA as non-hazardous, nonspillable for shipment by UPS or air transport.

Exclusive 4 year full limited warranty against factory defects materials or workmanship on PC 2150.

Exclusive pure-lead design (not gel) offers performance capabilities not available from conventional batteries.

Metal jacketed vs. Non-metal jacketed: The metal jacket is needed if it's being mounted near heat to protect the plastic of the battery from swelling. The lead plates are under much higher pressure than a lead acid battery and if the plastic heats up, the plates will want to expand outward which can ruin the battery if it doesn't have a jacket.

Cold Cranking Amps: For all the power, durability, and life of our technology, the cca ratings can seem disappointing. That's because the cca ratings are often misunderstood. Odyssey batteries are SLI (starting, lighting and ignition), so if you are looking for a starting or reserve battery the cold cranking numbers can be irrelevant.

The "standard" cca test measures the output of a battery for 30 seconds of crank at 0 degrees with the ending voltage of the battery being 7.2v. Some companies use 15 or 20 seconds and some companies use 32 degrees which can make for better results.

A vehicles starter isn't designed to withstand 30 seconds of cranking so we feel the batteries starting power is more important. The Odyssey part numbers represent the 5 second cranking power of the battery.

The PC680 is rated at 680 amps for 5 seconds, 595 amps for 10 seconds, and 525 amps for 20 seconds. Cranking power is even higher for the first four seconds. Similar sized lead acid batteries are only rated at 180 - 220 amps.