

日本东丽Toray反渗透膜TM720-400

产品名称	日本东丽Toray反渗透膜TM720-400
公司名称	苏州西尔环保科技有限公司
价格	4700.00/件
规格参数	滤膜类型:反渗透 (ro) 膜 品牌:东丽 适用对象:水
公司地址	中国江苏苏州吴中区东吴北路169号
联系电话	0512-66717525 15190050560

产品详情

identification			
tme	tm720-400		
productnumber			
article no.	tm720-400		
manufacturer			
brand	toray		
product image			
membrane			
membrane	toray tm 8"		
manufacturer type			
membranetype	reverse osmosis		
membrane	polyamide composite		
material			
short characterization	high productivity ro element for brackish water applications		
specification			
boron rejection sw @ ph 8 & 5 ppm feed	%		
membrane area	400 ft ²		
minimum rejection	99 %		
minimum permeate flow	31 m ³ /d		
membrane preservation	1000 ppm sodiumbisulfite solution		
specification sheet	080724_tm700.pdf		
boron rejection bw	%		

	@ ph 10 & 5 ppm feed		
	feed spacer thickness	mil	
	permeate flow	38.6 m ³ /d	
	rejection	99.7 %	
	test conditions		
	pressure	1.55 mpa	
	feed concentration nacl	2000 ppm	
	recovery	15 %	
	temperature	25 ° c	
	additional testconditions		
	ph	7	
	operating limits		
	max. feed pressure	4.1 mpa	
	max. feed temperature	45 ° c	
	max. sdi-15	5	
	max. chlorine in feed	0 ppm	
	feed ph range operation	2 - 11	
	feed ph range cleaning	1 - 12	
	max. dp / membrane	0.14 mpa	
	max. dp / vessel	0.4 mpa	
	dimensions		
	membrane diameter	8.0 "	
	length	40 "	
	permeate tube diameter	1.125 "	
	connection type	nd	
	technical drawing		
	application		
	feed water type	well water (brackish) tap water surface water (brackish)	
	membrane group	standard	
	application	industrial & process water brackish water treatment municipal / potable water	
	parts		

"供应日本东丽Toray反渗透膜TM720-400"的滤膜类型为反渗透(ro)膜, 品牌是东丽, 适用对象为水, 用途是水过滤, 规格为TM720-400, 厚度是20(mm), 适用范围为水过滤, 过滤方式是外压式, 性能为耐

酸,耐碱,操作压力是1.55 (MPa),工作温度为25 (),过滤精度是0.01NM,截留分子量为1000 (万),孔径是0.001 (μm),通量为120 (L/H),纵向强度是0.1 (MPa)