

荧光紫外老化试验箱 紫外光耐候试验箱 UV试验箱 UV-1

产品名称	荧光紫外老化试验箱 紫外光耐候试验箱 UV试验箱 UV-1
公司名称	深圳市鼎准电子有限公司
价格	118000.00/台
规格参数	加工定制:否 品牌:tops鼎准 型号:uv-1
公司地址	深圳市宝安区松岗街道罗田社区象山大道142号 象山湾工业园B栋4单元6层
联系电话	13928439421

产品详情

一. 设备简介device introduction:

紫外老化试验箱uv, 采用美国atlas紫外光管为光源, 通过改变、控制光辐照度、黑板温度、相对湿度、喷淋等方式, 模拟户外紫外线波段的光、热和降雨等综合条件, 对样品进行的人工加速老化试验. uv aging test chamber, using the united states atlas uv tube as a light source, through the change, control light irradiance, temperature, relative humidity, spray blackboard mode, simulated outdoor ultraviolet band of light, heat and rainfall condition, the samples were artificial accelerated aging test.

二. 适用标准applicable standard:

astm d4329 (plastic); iso 11507 (coating); iso 4892-1, astm g151, astm g154 ; en 927-6 (wood paint); en 1297 (roofing); iso11895, en1898, en 12224 (textile technology); en13523 (coil coatings); sae j2020 ; iso 11997-2

三. 设备规格device specification:

型号model	uv-1
辐照度控制方式irradiance control method	光辐照度可控irradiance can be set according to requirement
凝露方式condensation style	镍铬合金电水加热凝露系统nichrome heating gel system
光源light source	光源种类light source type 功率power
	uva or uvb荧光紫外光管 (american import , light life about 2000h) 40w/pcs

	波长范围wavelength range	uva:0.00 ~ 1.00 w/m2 uvb:0.00 ~ 1.15w/m2
构成	内壳材料inner materials	不锈钢板sus304# stainless steel plate sus304#
	空气加热air heating	镍铬合金加热nichrome heating
	水加热water heating	镍铬合金加热nichrome heating
	光管数量light qty.	the sample holder is made of
	操作控制系统control system	plc+lcd display touch screen (品牌brand:siemens)
	标准样板standard sample	24块标准试样架 (75 × 300mm,即两个75 × 150mm标准样品) the standard sample frame (75 × 300mm)
	凝露控制condensation control	凝露直接显示及自动控制condensation directly display and automatic
	循环方式circulation mode	光照、凝露、喷淋直接显示及自动控制light, condensation, spray directly automatic control
	光辐照度light irradiance	试验过程可设定光辐照度能量及时间test process can set light irradiance and time
喷淋水spray water	可调节与显示, 自动控制, 试验过程可设定喷淋时间adjustable and automatic control, test process can set the time of the spray	
	校准功能calibration function	温度自动校准, 方便、快速automatic temperature calibration, convenient and fast
外型尺寸extension size		1200 × 1500 × 450mm(w × h × d)
电源supply power		ac220/8a; 50/60hz; 2kw

"供应荧光紫外老化试验箱 紫外光耐候试验箱 UV试验箱 UV-1"的功率为40 (W) , 温度范围是/ () , 加工定制为否, 材质是不锈钢, 类型为紫外老化箱, 型号是UV-1, 工作室尺寸为1200 × 1500 × 450 (mm) , 适用范围是紫外光老化测试, 品牌为TOPS鼎准, 电源是220V