

		6	4	2	2	2	2	1	2
		0	0	7	7	7	2	5	0
		0	0	0	0	0	0	5	
k	1.4	6.9	9	1	1	2			
w	5	5	5	3	8.2				
	5	1	1	5					
	2.5	8	1	1	3				
	2			6	2	0			
				2					
r.	1	1	1	1	1	1	1	1	1
p.	5	5	5	5	5	5	5	5	5
	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0
	/	/	/	/	/	/	/	/	/
	3	3	3	3	3	3	3	3	3
	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0
k	0.1	2.4	4.4	4.4	6.9				
w	8	3	4	5	5	5	5	1	
	5	/	/	/	/	/	/	1	
	/	1.3	5.5	5.5	8	1			
	1.8	5	5	5					
	1								
	0.0	0.0	0.0	0.1	1.1	1.1			
	6	6	9	9	9	1	5	8	

尺寸参数

型号	a (mm)	b (mm)	c × d (mm)	e (mm)	f (mm)
10	270	750	1000 × 650	745	1350
50	320	950	1250 × 800	970	1650
150	420	1000	1350 × 800	1050	1750
200	520	1100	1650 × 850	1450	2050
250	550	1100	1650 × 850	1450	2050
300	550	1150	1700 × 900	1500	2200
400	670	1150	1860 × 1050	1650	2350
600	750	1250	2000 × 1050	1800	2400

"瑞美供应GHL250高速混合制粒机-干燥设备-制粒干燥设备-制粒机"的加工定制为是，品牌是瑞美，型号为250，适用物料是多种可用，应用领域为药厂，传热面积是20 (m²)，转速为800 (r/min)，功率是4.5 /5.5 (kw)，外形尺寸为1100/2050/855 (m)，重量是1300 (kg)