

Soundwin S400 VOIP 语音网关

产品名称	Soundwin S400 VOIP 语音网关
公司名称	深圳市安畅易科技有限公司
价格	4540.00/台
规格参数	品牌:soundwin 类别:语音 类型:无线
公司地址	深圳市宝安区新安街道2区龙井二路(宝安县糖烟酒公司大楼)3楼328室
联系电话	0755-88376590 15918785405

产品详情

	s400	s401	s402	s404	s200	s201	s202
ethernetport	4 lan + 1 wan						
telephony interface	quad rj-11				dual rj-11		
fxs/fxo	4fxs	3fxs+1fxo	2fxs+2fxo	4fxo	2fxs	1fxs+1fxo	2fxo
h.323 v2/v3/v4	ü	ü	ü	ü	ü	ü	ü
sip(rfc3261)	ü	ü	ü	ü	ü	ü	ü
smart-qos	ü	ü	ü	ü	ü	ü	ü
nat traversal	ü	ü	ü	ü	ü	ü	ü
echo cancellation	ü	ü	ü	ü	ü	ü	ü
g.711 a / μ -law	ü	ü	ü	ü	ü	ü	ü
g.723, g729ab	ü	ü	ü	ü	ü	ü	ü
t.38/t.30	ü	ü	ü	ü	ü	ü	ü
nat router	ü	ü	ü	ü	ü	ü	ü
dhcp server for private network	ü	ü	ü	ü	ü	ü	ü

产品介绍

2 -4 analog lines fxs/fxo voip gateway

telephony specification:

voice codec: g.711(a-law / μ -law), g.729 ab, g.723 (6.3 kbps / 5.3kbps)

fax support : t.30 / t.38

echo cancellation: g.165/g168

fxo caller id detection : dtmf and fsk(optional)

fxo hang up detection / anti-seized : tone learning automatically / manual tone

learning(optional)

answer supervision: support battery reverse detection and voice detection.

fxo answer delay time: support delay 0 — 8000 ms to answer.

adjustable ac termination impedance : 600 / 900 ohm and complex impedance

failsafe mechanism (fxs relay to fxo) : power failed bypass support / internet failed

bypass / registered failed bypass / unconditional bypass.

12k hz and 16k hz metering(customized)

ip specifications:

h.323 v2/v3/v4 and sip (rfc 3261) , sdp (rfc 2327), symmetric rtp,

stun (rfc3489), enum (rfc 2916), rtp payload for dtmf digits (rfc2833), outbound proxy support.

lan :support virtual server, dhcp server

wan: support pppoe client, dhcp client, fix ip address, ddns client

network address translation: providing build-in nat router function.

smart qos: guarantee the voice bandwidth

ip tos (ip precedence) / diffserv

call features

voice channels status display

direct dialing mode : peer to peer call (support ip address call or domain name call)

register call mode : register to sip proxy server or h.323 gatekeeper

adjustable volume : - 9 db ~ 9 db

silence compression / vad

auto dial for speed

dynamic jitter buffer

hot-line support

configuration & management

web-based graphical user interface

remote management over the ip network

ftp firmware upgrade

backup and restore configuration file

syslog client support

general specification

ac power : ac100v-240v, dc12v/1.5a,50/60 hz

temperature: 0 ° c ~ 40 ° c (operation)

humidity: up to 90% non-condensing

emission: fcc part 15 class b, ce mark

dimension : 260 x 130 x 35 mm

weight: 900g (aluminum)

"Soundwin S400 VOIP 语音网关"的品牌为soundwin , 类别是语音 , 类型为无线 , 配置接口是4