

# 思科IP电话系统 SPA400 4FXO网关

产品名称	思科IP电话系统 SPA400 4FXO网关
公司名称	深圳市福田区赛格电子市场蓝浦电子经营部
价格	440.00/台
规格参数	品牌:linksys 型号:spa400 类别:语音
公司地址	广东深圳市福田区赛格电子市场10楼10C22
联系电话	86 0755 33081994 13714361672

## 产品详情

思科ip电话系统

linksys spa400+ spa9000 支持4条外线。

注意事项：spa400 usb口只能接信箱，不能接其它usb产品，不然烧坏产品。

linksys spa400 4fxo 语音网关

spa9000绝配产品，国内少有。。。

spa400为全新货品，spa400的配件有spa400一个，电源一个，语音信箱一个。

设置方法：

cisco linksys 4fxo 网关 ， ip pbx9000 绝配

带 voicemail module

，功能是好的。

spa400 voice mail with 4fxo for ip pbx spa9000

linksys spa400

featuresconnects 4 analog pstn lines to your voip network4 rj-11 fxo portsintegrated voicemail application serverenables spa9000 ip phone clients to leave and playback voicemailusb 1.1 host interface for the voicemail module

and application configure up to 32 voicemail accounts caller id detection hunt grouping of fxo ports advanced inbound and outbound call routing independent configurable dial plans to utilize multiple service providers 8 leds: power, status, lan, ports 1-4, usb external switching power adapter 5v dc/2a

package contents 1 - spa400 1 - power adapter 1 - usb 1.1 voicemail module 1 - rj45 ethernet cable 4 - rj11 telephone cables 1 - quick installation guide

specifications

model spa400: \* note: many specifications are programmable within a defined range or list of options. please see the spa administration guide for details. the target configuration profile is uploaded to the spa400 at the time of provisioning.

standards: ieee 802.3 (10base-t), ieee 802.3u (1000base-t)

cabling type: rj45 ethernet category 5, rj11 standard phone cable

leds: power, status, lan, port 1-4, usb

voice protocols: session initiation protocol (sip v2)

voice algorithms: g.711 a-law and  $\mu$ -law g.726, g.729 a bdtmf: in-band (rfc 2833) call progress tone generation echo cancellation (g.168) jitter buffer - adaptive vad - voice activity detection call progress tone generation comfort noise generation frame loss concealment

provisioning, administration & maintenance: web browser administration & configuration via integral web server telnet access to command line interface automated provisioning & upgrade via http non-intrusive, in-service upgrades report generation & event logging system fault self-test

security: password protected system reset to factory default password protected admin and user access authority

physical interfaces: 1 100base-t rj-45 ethernet port (ieee 802.3) 1 usb 1.1

"思科IP电话系统 SPA400 4FXO网关"的网络接口为WAN，配置接口是2RJ11，网管方式为WEB，话机接口是4，类型为有线，型号是SPA400，储存量为其他，类别是语音，传真精度为SIP，传真速率是100，品牌为linksys，质保是一年