

AAC1115喇叭 goyo

产品名称	AAC1115喇叭 goyo
公司名称	绵阳市歌阳电子有限公司
价格	2.00/PCS
规格参数	加工定制:是 品牌:goyo 型号:1115
公司地址	三台县新鲁镇场镇
联系电话	15982968399 18823213287

产品详情

1. scope this document contains required environmental, electrical, acoustic, mechanical, package and reliability test requirements. 2. environmental requirement the transducer including all components and solder joints must be free from lead (pb) and other banned or restricted substances according to customer's requirements. 3. electrical requirements 3.1 rated impedance $8 \pm 15\%$ ohms @2khz, 1vrms input 3.2 rated noise power (in 1cc box) 0.5 watts 3.3 short term maximum power (in 1cc box) 0.7 watts 4. acoustical requirements 4.1 sound pressure level 85 ± 3 db @1v/10cm at flat range 4.2 bass resonance frequency in free air $600 \pm 20\%$ hz, 1v input 4.3 rated frequency range 200 - 10khz frequency response see figure 14.4 thd $< 10\%$ @ 1khz, 1v input 4.5 rub & buzz the input power shall be set at rated noise power with specified back cavity. using an audio oscillator sweep from 200 to 3000hz . there shall be no buzzes, rattles, nor spurious noises. 5. polarity requirements 5.1 polarity when a dc source s "+" polarity is attached to the "signal"— marked in "+" and the "-" polarity is attached the "gnd", the membrane will move forward. 5.2 magnetic polarity top of the magnet is the north pole.

"供应AAC1115喇叭"的输出阻抗为 $7.5 \pm 15\%$ ，频率响应是 $620 \pm 15\%$ ，种类为送、受话器，加工定制是是，材质为LCP，型号是1115，规格尺寸为11*15（mm），品牌是GOYO，驱动方式为电动式(动圈式)，灵敏度是 85 ± 3 dB